

Global Information Assurance Certification Paper

Copyright SANS Institute Author Retains Full Rights

This paper is taken from the GIAC directory of certified professionals. Reposting is not permited without express written permission.

Interested in learning more?

Check out the list of upcoming events offering "Security Essentials: Network, Endpoint, and Cloud (Security 401)" at http://www.giac.org/registration/gsec

Preventing Your Computer From Becoming a Zombie

Jamy Klein June12, 2001

Introduction

The advent of always on Internet connections has created a large community of users with high bandwidth connections and little to no security. Hackers, crackers and "script kiddies" increasingly target these users. The machines themselves are not usually a target for data theft, but instead are targeted for use as drones in attacks on other systems.

On February 7, 2000, a wave of Distributed Denial of Service (DDoS) attacks hit high profile websites such as Yahoo and Amazon.com taking them offline. Many of the attacks were traced back to compromised machines at universities infected with a zombie agent. A zombie agent is used to remotely control a compromised machine to carry out attacks. A zombie agent, is a Trojan used to control a user's machine without their knowledge.

Compromised computers on various networks carried out a more recent attack against the security web site of Gibson Research Corporation at <u>www.grc.com</u>. The majority of attacks originated on compromised cable modem connected computers on the @home® network. Steve Gibson, the owner of <u>www.grc.com</u> has posted a detailed transcription of the attacks and his communications with the attackers at <u>http://grc.com/dos/grcdos.htm</u>.

A recent study conducted by the University of California, San Diego determined that approximately 4,000 Denial of Service or DoS attacks take place each week. (<u>http://www.cnn.com/2001/TECH/intemet/05/24/dos.study.idg/index.html</u>) With the amount of attacks taking place, users need to take action to protect their computer data and to prevent the use of their systems in attacks against others.

What is a Trojan anyway?

The tech website <u>www.whatis.com</u> defines a Trojan with the following:

"In computers, a Trojan horse is a program in which malicious or harmful code is contained inside apparently harmless programming or data in such a way that it can get control and do it's damage, such as ruining the File Allocation Table on your hard disk."

In the examples given above the hackers were not concerned with attacking the individual users machines. The Trojans were instead used to take control of a user's machine and Turn it in to a Zombie. A zombie is a compromised machine that is used to carry out denial of service attacks against other sites or machines.

Once a hacker has control of your system, he is free to use it as he sees fit. The hacker can install programs, delete files, send messages, and carry out attacks on others.

Am I really at risk?

Recently I moved to cable modem access. After reading all the stories about DDoS attacks and compromised home computers I wanted to see if the volume of attacks was accurate, and to see if unscrupulous hackers really were interested in my system. As a test I set up one of my machine with Windows NT workstation 4.0 and installed Black ICE defender, a personal firewall and intrusion detection application that I had heard about on Tech TV news. I than connected it to the cable modem. It should be noted that I do not specifically recommend Black ICE Defender as it has numerous limitations (for specific information on these limitations see www.grc.com), it is used here as it does contain one of the most easily understood logging facilities of the current personal firewalls. Within hours I had numerous attempts to scan and access my system as shown by the screen capture below.

	105			
BlackICE by Network	ICE			
e Tools Help				
tacks Intruders History	[Information]			
1 1 1	1			
Time	Attack	Intruder	Count	
🗕 2001-05-27 20:18:42	TCP OS fingerprint	61.140.73.131	1	
🗕 2001-05-27 20:17:34	RPC port probe	wrack.thatsnice.org	1	
🗕 2001-05-27 19:32:40	RPC port probe	211.42.183.77	1	
🗕 2001-05-27 18:39:16	DNS port probe	210.177.74.193	1	
📡 2001-05-27 18:13:51	NNTP port probe	authorized-scan1.security	10	
🗕 2001-05-27 17:54:38	TCP port probe	MR.COMPUTER	8	
🗕 2001-05-27 17:52:53	RPC port probe	210.179.229.253	1	
🗕 2001-05-27 17:50:12	RPC port probe	u97-197.u203-204.giga.r	1	
🗕 2001-05-27 17:17:29	TCP port probe	MR.COMPUTER	5	
🗕 2001-05-27 17:17:29	TCP port probe	MR.COMPUTER	1	
🗕 2001-05-27 17:17:28	TCP port probe	MR.COMPUTER	2	
🗕 2001-05-27 17:17:27	TCP port probe	MR.COMPUTER	3	
2001-05-27 17:16:55	TCP port probe	MR.COMPUTER	1	
🗕 2001-05-27 16:35:37	SubSeven port probe	c157256-a.shlls1.pa.hom	3	
2001-05-27 15:33:15	TCP port probe	gso26-207-011.triad.rr.co	3	
🗕 2001-05-27 13:48:38	TCP port probe	MR.COMPUTER	2	-
	· · · · · · · · · · · · · · · · · · ·	e 1 11		
elect an Attack and a de	scription of that Attack will be	displayed here.		advICE
			<u>C</u> lose	<u>H</u> elp

You will notice that on the date of 2001-05-27, between the hours of 1:48pm and 8:18pm BlackICE logged 16 unique attempts to access my machine. As shown by the count column, some of these attacks were tried multiple times. The types of attacks varied from a simple TCP Port ping to a scan for the Subseven Trojan.

The intruder listed, as Mr.Computer is one of my machines that I used to scan the machine running BlackICE from my internal network. The intruder listed as authorized-scan1.security is actually authorized-scan1.security.home.com, my ISP scans port 119 for Network News Transfer Protocol (NNTP) as running a newsgroup server is a violation of the Acceptable Use Policy (AUP).

To see if your computer is inflicted with a Trojan you can run netstat -an at your command prompt. The –a parameter displays all connections and –n displays the addresses in numerical form. Netstat will list all open ports on your system including legitimate connections. Netstat will not show what application is using each port, but you can compare open port's to a list of know Trojan ports at http://www.doshelp.com/trojanports.htm. For example in the past ports 6711 - 6713 were known to be ports for the Subseven Trojan. The known ports for certain Trojans are a good place to start, but many Trojans are now able to use any port, and as a result it is better to use netstat to look for any unexpected traffic. In addition to netstat, you can also use a port scanner to determine open ports, many are available at http://www.cots.com/tools/pscan.htm. If you are using Windows NT or 2000, Foundstone.com has a free utility called Fport that will map open ports to applications.

Below is a sample of netstat's output.

Active Connections

Proto	Local Address	Foreign Address	State	•
TCP	computer:1078	MR.COMPUTER	R: 0	LISTENING
TCP	computer:1027	cs8.msg.yahoo.co	m:5050	TIME_WAIT
TCP	computer:137	MR.COMPUTER	:0	LISTENING
TCP	computer:138	MR.COMPUTER	:0	LISTENING
TCP	computer:nbsession	MR.COMPUTE	ER:0	LISTENING
UDP	computer:1078	*:*		
UDP	computer:nbname	*:*		
UDP	computer:nbdatagra	um *:*		
	-			

How do Trojans arrive on my system?

The most common ways to have your computer infected by a Trojan are as follows:

<u>Email:</u>

The Trojan arrives as an attachment disguised as a useful program or even embedded inside another program.

Theoretically with the advent of self-executing viruses such as Melissa, the Trojan could potentially deploy itself without the user consciously executing it. In the case of the

Meliss a virus and Microsoft outbok, Melissa was written in Visual Basic script, which Outbok will execute in the preview pane by default.

Local Installation:

Someone could potentially install a Trojan while physically sitting at your machine, from a floppy disk, CD-ROM, or other removable media. For example: even if you have a screen saver that locks your computer with a pass word, anyone could insert a CD in your CD-ROM and have it automatically open the CD and install programs.

Web Sites:

A Trojan could also be installed from a website through a malicious Active-x or Java applet. Java and Active-x code have the ability to execute programs off of a website as if it were installed locally on your computer. In the case of Active-X, the programs execute locally on your system with full administrative privileges.

A Trojan could also be hidden on a website in a file that appears to be a useful program. For instance, you download the newest free game, Elf Bowling 12 and play. While unknown to you, it is secretly transferring files from your pc to a server on the Internet or worse; it's using your Internet connection to flood the connection of another user or site.

What can I do to prevent my machine from being used as a Zombie? Isn't virus Protection enough?

In recent months some Trojans have been reclassified as remote administration took. The most glaring example is Back Orifice. Many Trojans are also purposely taking steps to hide themselves from anti-virus took. And as a result you should not rely on an anti-virus tool alone. Instead you should practice the philosophy of defense in depth, by utilizing multiple security tools and minimizing actions that could put your system at risk.

<u>Email:</u>

- 1. Ensure you are running the latest version of your preferred email client.
- 2. Disable any auto preview features on your email client.
- 3. Do not open attachments if you cannot verify the origin of the file as having been sent from a source you trust.
- 4. If you run Microsoft Outlook, install the attachment security update from the following site:

http://www.microsoft.com/PressPass/press/2000/May00/SecurityUpdatePR.asp

5. Disable any scripting features, to prevent any hidden scripts from executing.

Local Installation:

1. Ensure that you do not access disks unless it is from a trusted source such as prepackaged software.

- Disable the auto run feature of your CD-ROM drive. Instructions for disabling auto run in Microsoft Windows can be found at the following URLs <u>http://support.microsoft.com/support/kb/articles/Q126/0/25.asp</u> or <u>http://msdn.microsoft.com/library/psdk/shellcc/shell/Shell_basics/Autoplay_reg.h</u> tm
- 3. When you are away from your machine protect it with a pass word.

Web Sites:

- 1. Enable Active-X and Java filtering in your web browser.
- 2. Run a virus protection application such as McAfee Virus Scan that protects against malicious Active-X and Java applets.
- 3. Scan all downloaded files with a virus protection application.

Firewall:

1. Install and run an application level personal firewall. Also try to use a Firewall such as Tiny Software Personal Firewall (available at <u>www.tinysoftware.com</u>, free for personal use) that uses an encryption algorithm such as MD5 to verify that any application allowed through has not been modified. As of this writing the only two firewalls that are know to perform application integrity checking, they are Zonelabs' Zonealarm (<u>www.zonelabs.com</u>) and Tiny software's personal firewall. Test the firewalls encryption support with the Leaktest application available at <u>www.grc.com</u>.

Some firewalls provide a facility that will show what ports are open and the particular application that is using them. Below is a screen capture of another useful feature of Tiny Personal Firewall's Status Window. As you can it is a very useful feature that maps all open ports to applications. I have not found any other firewall product that implements this functionality.

🙀 Tiny Personal Fire	ewall - Ope	ned Connections at lo	calhost			_1	
File Logs Settings	Help						
Application	Protocol	Local Address	Remote Address	State	Creation Time	Rx [Bytes] R:	xS▲
DNS.EXE	UDP	localhost:1027		Listening	2.6.2001 14:27:43	0	
DNS.EXE	UDP	192.168.0.251:53		Listening	2.6.2001 14:27:43	0	
DNS.EXE	UDP	localhost:53		Listening	2.6.2001 14:27:43	0	
DNS.EXE	UDP	all:1028		Listening	2.6.2001 14:27:43	0	
DNS.EXE	TCP	all:53		Listening	2.6.2001 14:27:43	0	
DNS.EXE	TCP	all:1029		Listening	2.6.2001 14:27:43	0	
EXPLORE.EXE	UDP	localhost:1043		Listening	2.6.2001 14:31:04	277	
EXPLORE.EXE	UDP	localhost:1064		Listening	2.6.2001 14:33:56	188	
INETINFO.EXE	TCP	all:1031		Listening	2.6.2001 14:27:46	0	
INETINFO.EXE	TCP	all:80		Listening	2.6.2001 14:27:53	0	
INETINFO.EXE	UDP	all:3456		Listening	2.6.2001 14:27:53	12	
INETINFO.EXE	TCP	all:443		Listening	2.6.2001 14:27:53	0	
INETINFO.EXE	TCP	all:8525		Listening	2.6.2001 14:29:24	0	
INETINFO.EXE	UDP	all:1035		Listening	2.6.2001 14:29:25	0	
INETINFO.EXE	TCP	all:25		Listening	2.6.2001 14:29:25	0	
LSASS.EXE	UDP	192.168.0.251:500		Listening	2.6.2001 14:29:25	0	
MSDTC.EXE	TCP	all:3372		Listening	2.6.2001 14:27:31	0	
MSDTC.EXE	TCP	all:1025		Listening	2.6.2001 14:27:30	0	-
•							•
TCP Listening: 15	TCP Conne	cted: 6 UDP Listen	ing: 17	Tot	al Rx speed: 13.14	Total Tx speed: 13.1	4 //.

- 2. Ensure that your firewall logs both incoming and outgoing traffic.
- 3. Periodically check your firewall with security tests such as Shields Up at <u>www.grc.com</u> and <u>http://www.dslreports.com/scan</u>. Below is sample output from both tests.

Grc.com Shields Up: With this service, you should ensure that you do not have any ports listed as open. Be aware that even if your machine is listed as not having any ports open you should not feel that you have no security concems, as Shields Up! only scans 10 ports of the total 65535 TCP/IP ports.

X Shields U	P! Port	Probe - Nets	саре		_ 🗆 ×
Eile Edit Vie Back	ew <u>Go L</u> Sorward	⊊ommunicator 3 Reload I	Help Marken and Alexandree Alexandree Marken Alexandree	nch Guide Prímt Security Stop Netscape	0
👔 🦋 Bool	kmarks 🤞	Location: htt	p://grc.com/x/	/ne.dll?rh1ck2l2	it's Related
🕴 🥝 Local	Info @ 1	Fop Sites 📿	How Do I? (Member Services @ Help @ Chat IS NOW DEING PRODECT. Please Stand Dy	
	Port	Service	Status	Security Implications	
	21	FTP	Stealth!	There is NO EVIDENCE WHATSOEVER that a port (or even any computer) exists at this IP address!	
	23	Telnet	Stealth!	There is NO EVIDENCE WHATSOEVER that a port (or even any computer) exists at this IP address!	
	25	SMTP	Stealth!	There is NO EVIDENCE WHATSOEVER that a port (or even any computer) exists at this IP address!	
	79	Finger	Stealth!	There is NO EVIDENCE WHATSOEVER that a port (or even any computer) exists at this IP address!	
	80	нттр	Stealth!	There is NO EVIDENCE WHATSOEVER that a port (or even any computer) exists at this IP address!	
	110	POP3	Stealth!	There is NO EVIDENCE WHATSOEVER that a port (or even any computer) exists at this IP address!	
	113	IDENT	Stealth!	There is NO EVIDENCE WHATSOEVER that a port (or even any computer) exists at this IP address!	
	139	Net BIOS	Stealth!	There is NO EVIDENCE WHATSOEVER that a port (or even any computer) exists at this IP address!	
	143	IMAP	Stealth!	There is NO EVIDENCE WHATSOEVER that a port (or even any computer) exists at this IP address!	
	443	HTTPS	Stealth!	There is NO EVIDENCE WHATSOEVER that a port (or even any computer) exists at this IP address!	-
		Document	Done		 ///

DSLReports.com: The free version of Ds lreports security scan executes some common attack scripts that hackers use against your firewall in addition to scanning 2086 ports including all 1024 of the well-known ports. Information on the paid version can be found at <u>http://www.dslreports.com/secure_features</u>.

Back Powerd Relad Powerd Guide Powerd Relation Powerd Relation Powerd Relation	DSL - DSLreports.com File Edit View Go Comr	- the place for BROAD municator <u>H</u> elp	BAND - Netscape	_ 🗆 ×
Bookmaks & Location: http://www.dikepots.com/scar/b80ae143eb4/219d361559/31003d4d3 Continue Control of the Security of the Security of Cable/DSL networks Security for Cable/DSL networks Security for Cable/DSL networks Conclusion: Possible Problem I We did get information from scanning your ports, this information could encourage attackers to probe further. Do you know why you are advertising these services to the net? perhaps installation of a firewall, or reconfiguration of your firewall to be more secure, would provide peace of mind. Whole work to obctor/Prig Wate Me Obcote work: For Providers About us glossary: If points and the points (open or closed) to an open request was received. TCP 138 Is FILTERED No response (open or closed) to an open request was received. TCP 1080 Is FILTERED No response (open or closed) to an open request was received. ALL UDP FILTERED No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. Secure date was received. ALL UDP No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. Secure date date date open or closed) to an open request was received. Secure date date date open or closed) to an open request was received. Secure date date date date date date date dat	Back Forward R	3 🏠 🧀	ch Guide Print Security Stop Netscape	0
Conclusion: Possible Problem! We did get information from scanning your ports, this information could encourage attackers to probe further. Do you know why you are advertising these services to the net? perhaps installation of a firewall, or reconfiguration of your firewall to be more secure, would provide peace of mind. Conclusion: Possible Problem! We did get information from scanning your ports, this information could encourage attackers to probe further. Do you know why you are advertising these services to the net? perhaps installation of a firewall, or reconfiguration of your firewall to be more secure, would provide peace of mind. Other TCP CLOSED We received a response that this port was closed. TCP 135 is OPEN We have no specific hints for this port number just yet. We are monitoring results though, and we add advice for port numbers that come up frequently. TCP 137 is FILTERED No response (open or closed) to an open request was received. TCP 138 No response (open or closed) to an open request was received. TCP 138 No response (open or closed) to an open request was received. TCP 138 No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. ALL UDP	🧵 🍕 Bookmarks 🧔 L	ocation: http://www.dslrep	orts.com/scan/b80ae143eb4f219d961555f31003dd49 🔽 🌍 🐨 What	's Related
 Section y for CableOSE networks Premium Speed Conclusion: Possible Problem! We did get information from scanning your ports, this information could encourage attackers to probe further. Do you know why you are advertising these services to the net? perhaps installation of a firewall, or reconfiguration of your firewall to be more secure, would provide peace of mind. Other TCP CLOSED We received a response that this port was closed. TCP 135 is OPEN we add advice for part numbers that come up frequently. TCP 137 is FILTERED No response (open or closed) to an open request was received. TCP 138 is FILTERED No response (open or closed) to an open request was received. TCP 138 is FILTERED No response (open or closed) to an open request was received. TCP 138 is FILTERED No response (open or closed) to an open request was received. TCP 138 is FILTERED No response (open or closed) to an open request was received. TCP 138 is FILTERED No response (open or closed) to an open request was received. TCP 138 is FILTERED No response (open or closed) to an open request was received. TCP 138 is FILTERED No response (open or closed) to an open request was received. 	🖉 🥝 Local Info 🙆 Top	Sites @ How Dol? 🤇	Member Services @ Help @ Chat	
 Col. Dary Line Guality Security Hetory Line Monitor Octoring Score Watch Roder Watch Port Scan Buy For Providers About us glossary: Col 139 No response (open or closed) to an open request was received. TCP 138 Is FILTERED No response (open or closed) to an open request was received. TCP 138 No response (open or closed) to an open request was received. ALL UDP FiltERED No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. Score Piltered No response (open or closed) to an open request was received. 	Speed Tests Premium Speed	Security for Cable.		<u></u>
 Security History History Line Montor DoctorFing Wate Me Whote Other TCP CloseD We received a response that this port was closed. TCP 135 We have no specific hints for this port number just yet. We are monitoring results though, and we add advice for port numbers that come up frequently. TCP 137 Is OPEN No response (open or closed) to an open request was received. TCP 138 Is FILTERED No response (open or closed) to an open request was received. TCP 10800 No response (open or closed) to an open request was received. FILTERED No response (open or closed) to an open request was received. So response (open or closed) to an open request was received. So response (open or closed) to an open request was received. No response (open or closed) to an open request was received. So response (open or closed) to an open request was received. So response (open or closed) to an open request was received. So received. So received. So response (open or closed) to an open request was received. So response (open or closed) to an open request was received. So response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. 	DSL Diary Line Quality		Your IP Address	
• Note • Note • Router Watch • Port Scan Buy TCP 135 We have no specific hints for this port number just yet. We are monitoring results though, and we add advice for port numbers that come up frequently. About us TCP 137 No response (open or closed) to an open request was received. If CP 138 No response (open or closed) to an open request was received. TCP 139 Is FILTERED No response (open or closed) to an open request was received. TCP 139 Is FILTERED No response (open or closed) to an open request was received. TCP 138 No response (open or closed) to an open request was received. TCP 138 No response (open or closed) to an open request was received. TCP 138 No response (open or closed) to an open request was received. TCP 1080 No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received.	Security History Line Monitor DoctorPing Vvake Me	Conclusion: F encourage attack installation of a fir	Possible Problem! We did get information from scanning your ports, this information could ers to probe further. Do you know why you are advertising these services to the net? perhaps ewall, or reconfiguration of your firewall to be more secure, would provide peace of mind.	
Buy TCP 135 We have no specific hints for this port number just yet. We are monitoring results though, and we add advice for port numbers that come up frequently. About us TCP 137 No response (open or closed) to an open request was received. TCP 138 No response (open or closed) to an open request was received. TCP 139 No response (open or closed) to an open request was received. TCP 139 No response (open or closed) to an open request was received. TCP 1080 No response (open or closed) to an open request was received. TCP 1080 No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received.	 Whois Router Watch Port Scan 	other TCP CLOSED	We received a response that this port was closed.	
About us TCP 137 is FiLTERED No response (open or closed) to an open request was received. TCP 138 is FiLTERED No response (open or closed) to an open request was received. TCP 139 is FILTERED No response (open or closed) to an open request was received. TCP 1080 is FILTERED No response (open or closed) to an open request was received. ALL UDP FILTERED No response (open or closed) to an open request was received.	Buy For Providers	TCP 135 is OPEN	We have no specific hints for this port number just yet. We are monitoring results though, and we add advice for port numbers that come up frequently.	
TCP 138 No response (open or closed) to an open request was received. TCP 139 No response (open or closed) to an open request was received. TCP 1080 No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received.	dbout us	TCP 137 is FILTERED	No response (open or closed) to an open request was received.	
TCP 139 No response (open or closed) to an open request was received. TCP 1080 No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. FILTERED No response (open or closed) to an open request was received.	GO	TCP 138 is FILTERED	No response (open or closed) to an open request was received.	
TCP 1080 No response (open or closed) to an open request was received. ALL UDP No response (open or closed) to an open request was received. FILTERED No response (open or closed) to an open request was received.		TCP 139 is FILTERED	No response (open or closed) to an open request was received.	
ALL UDP No response (open or closed) to an open request was received. FILTERED No response (open or closed) to an open request was received.		TCP 1080 is FILTERED	No response (open or closed) to an open request was received.	
		ALL UDP FILTERED	No response (open or closed) to an open request was received.	
Or THE ACCESS CORP. O		Document: Done	@ 1999,2000,2001 dsireports. Bandwidth by Net Access Corp. fea	edback

MD5 encryption sounds great, but how does it work?

MD5 is an acronym for Message Digest Algorithm and was developed by Ron Rivest, and is now owned by RSA (<u>www.rsa.com</u>). RSA is well known for their implementation of the triple DES algorithm. MD5 is the third version of the RSA MD algorithm. The MD algorithm was originally developed to allow messages to be sent securely back and forth between recipients, ensuring any third parties did not alter the contents.

MD5 is a symmetric key block cipher algorithm, meaning it encrypts data in 512- bit blocks and outputs a single 128-bit "message digest". MD5 does this by separating the data into 512-bit blocks. If the data ends with less than a 512-bit block, the algorithm "pads" the data by adding extra bits until it is a full 512-bit block. Next MD5 applies a 64 –bit representation of the original data to the end of the padded data. Third MD5 initializes the MD (message digest) buffer and with 4 predefined 32-bit register values. Fourth, MD5 applies its encryption algorithm to each block. As a result, each file should have it's own unique signature. The precise workings of each MD5 step are beyond the scope of this paper. To read about the process and view the algorithm, see RFC 1321.

The benefit to this technique is that it should be virtually impossible for any program to impersonate another program. This behavior when implemented properly in a security product will also prevent non-registered programs from traversing the firewall to the Internet. An example of how Tiny Personal Firewall uses the MD5 signature is below.

1. First we configure Tiny firewall to allow Internet explorer (iexplore.exe) to access the Internet. As shown below.

Tiny Person	al Firewall	
٢	Outgoing Connection Alert!	
Time:	02/Jun/2001 17:53:42	
Remote:	msn.net [207.46.179.143], port 80 - TCP	
Details:	'Internet Explorer' from your computer wants to connect 🔺 to msn.net [207.46.179.143], port 80	
	Details about application	
Ø	c:\program files\internet explorer\iexplore.exe	
	Permit Deny	
🔽 Create	appropriate filter rule and don't ask me again	
Cus	tomize rule	

2. Tiny creates a unique MD5 signature for iexplore.exe.

Firewall Configuration		×
Filter Rules Miscellaneous Application's MD5		
Application C:\WINNT\SYSTEM32\INETSRV\INETINFD.EXE C:\WINNT\SYSTEM32\SERVICES.EXE C:\PROGRAM FILES\TOOLS FOR SELLING\TIME SYNCHRO\TSYN.EXE C:\PROGRAM FILES\INTERNET EXPLORERVEXPLORE.EXE	Md5 (BINARY) 05850 20 8000F76A84A1D 2281FA603E C8 63709F4C5BD 98 401 849C929D 6E EFB83D 42C5AE 4D 89086958335A4496A71BD EC6 5235F5138655C99F780F0E026A8A8774A	
Delete Check MD5 Signature		
	OK Cancel Apply	

3. To test the MD5 signature, I renamed netscape.exe to iexplore.exe, and tried to access the Internet. Tiny blocked the renamed netscape.exe as shown below.

Tiny Person	nal Firewall	
٢	Outgoing Connection Alert!	
Time:	02/Jun/2001 17:55:48	
Remote:	home-v5.websys.aol.com [64.12.151.216], port 80 - TCP	
Details:	Netscape Navigator application file' from your computer wants to connect to home-v5.websys.aol.com [64.12.151.216], port 80	
	Details about application	
N	c:\program files\netscape\communicator\program\iexplore.exe	
	Permit Deny	
Create	appropriate filter rule and don't ask me again	
Cus	stomize rule	

4. Next I viewed the MD5 signature window to verify that Tiny did in fact create a new signature for the renamed netscape.exe. As you can see, both filenames are identical, but the MD5 signatures are different.

irewall Configuration		×
Filter Rules Miscellaneous Application's MD5		
Application C:\WINNT\SYSTEM32\INETSRV\INETINF0.EXE C:\WINNT\SYSTEM32\SERVICES.EXE C:\PROGRAM FILES\TOOLS FOR SELLING\TIME SYNCHRO\TSYN.EXE C:\PROGRAM FILES\INTERNET EXPLOREN\EXPLORE.EXE C:\PROGRAM FILES\INETSCAPE\COMMUNICATOR\PROGRAM\IEXPLOR	Md5 (BINARY) 0585D2D8000F76A84A1D2281FA603EC8 63709F4C5BD9B401849C929D6EEFBB3D 42C5AE4DB9086958335AA496A71BDEC6 5235F513B65C99F780F0E026A8A8774A FD9050AC3A7C444F8558A0566F0BAF56	
Delete Check MD5 Signature		
	OK Cancel Apply	

Summary

Even though no "silver bullet" solution exists to stop personal computers from being used as zombies, you can effectively minimize this abuse. Utilizing a firewall on your computer, and following these simple prevention tips you can minimize the risks of having your computer or computer's you manage used as a zombie in attacks against others.

References

Avert Research Center http://www.mcafeeb2b.com/naicommon/avert/avert-research-center/default.asp

Costello, Sam. "Study: Nearly 4,000 DoS Attacks Occur Per Week" http://www.cnn.com/2001/TECH/internet/05/24/dos.study.idg/index.html

COTSE http://www.cotse.com/took/pscan.htm

DoSHelp.com:Intrusion & Attack Reporting Center http://www.doshelp.com/trojanports.htm

Gibson Research Corporation

Microsoft TechNet www.microsoft.com

RFC 1319 & 1321 http://www.cis.ohio-state.edu/cgi-bin/rfc/rfc1319.html http://www.cis.ohio-state.edu/cgi-bin/rfc/rfc1321.html

Symantec AV Center <u>http://www.symantec.com/avcenter/</u>

System Administration and Network Security Institute www.sans.org

Tiny Software Company www.tinysoftware.com

"What are MD2, MD4, and MD5" <u>http://www.rs.asecurity.com/rs.alabs/faq/3-6-6.html</u>

Whatis ?com www.whatis.com