

Global Information Assurance Certification Paper

Copyright SANS Institute Author Retains Full Rights

This paper is taken from the GIAC directory of certified professionals. Reposting is not permited without express written permission.

Interested in learning more?

Check out the list of upcoming events offering "Hacker Tools, Techniques, and Incident Handling (Security 504)" at http://www.giac.org/registration/gcih

Learning Cryptography by Doing It Wrong: Cryptanalysis of the Vigenère Cipher

GIAC (GCIH) Gold Certification

Author: Jeremy Druin, jdruin@gmail.com Advisor: Christopher Walker, CISSP, CCISO, GCED, GWEB Accepted: 2/1/2018

Abstract

When studying complex ideas, it may help to begin with a simpler example to better understand its concepts. Modern cryptography and cryptanalysis are exceptionally complex, so a case study from classical cryptography can aid understanding. The Vigenère Cipher is a good example. Vigenère was widely considered to be a secure cipher for three centuries. It is non-trivial to cryptanalyze, offering a stretch goal for beginners, but not impossible to comprehend. Vigenère provides practice of multiple techniques such as statistical analysis, histograms, and Index of Coincidence. Statistical properties of files before and after encryption can be compared to show attributes that allow encrypted files to be detected. A method of detecting the encryption key length for a Vigenère cipher will be introduced. Ultimately, a strategy to recover the key for JPEG encrypted files will be demonstrated. To help the reader follow this analysis, open source software will be provided that performs encryption, decryption, and cryptanalysis. Besides learning about classical ciphers and having fun, we will reinforce the importance of proper cipher choice for the modern InfoSec professional.

1. Introduction

Cryptography, the art and science of secret writing (Merriam-Webster, 2017), is a vast and complex topic. Cryptography includes cryptanalysis techniques, the practice of deciphering or decoding encrypted messages (Collins English Dictionary, 2012). Some practical understanding of cryptanalysis techniques is important for cyber security practitioners. While advanced cryptanalysis is difficult to learn without significant time and talent, classical cryptographic ciphers are within reach of the non-professional. Specifically, simple substitution and polyalphabetic ciphers provide an introduction into cryptanalysis and demonstrate the importance of proper implementation.

Modern ciphers are significantly more advanced than the classical Vigenère cipher. A study of Vigenère is not an analog to taking on strong ciphers such as Advanced Encryption Standard (AES). The underlying cryptosystem, its mechanisms and therefore approach to attack are different (NOVER, 2004). However, Vigenère provides a good opportunity to explore and practice cryptanalysis techniques. Vigenère is non-trivial to cryptanalyze and was once widely considered unbreakable (Norman, 2017). Yet by combining multiple techniques and employing computers, Vigenère can be broken by persistent amateurs.

Two tools are provided to allow the reader to follow the examples provided in this paper. One provides encryption and decryption of files using a Vigenère cipher. The second tool, a frequency analyzer, performs statistical analysis, can determine the Vigenère encryption key length, and decrypt a file given the key. The analysis begins by comparing files before and after encryption. Statistic properties that indicate potentially weak encryption are noted. It will be shown how a Vigenère cipher can be broken if the length of the encryption key is found. Further investigation will present a method to determine the key length. Finally, the key will be recovered.

2. Overview

Monoalphabetic ciphers pick a key from a single alphabet. A single key is used to encrypt each character of plaintext. This leaves the ciphertext vulnerable to cryptanalysis via frequency analysis (Daniel Rodriguez-Clark, 2013). A form of these simple substitution ciphers was used

by the armies of Julius Caesar as early as 50 B.C. (Simmons, 2009). The monoalphabetic cipher with key = 3 is called a "Caesar Cipher" as a result.

Polyalphabetic ciphers such as Vigenère use an independent key to encrypt each character of plaintext until the end of the key is reached. At this point, the key is reused for the next block of plaintext characters (Math Explorers Club, 2003). The Vigenère cipher, a polyalphabetic cipher, is attributed to Blaise de Vigenère (Simmons, 2009) in 1586 but may have been reinvented multiple times (Norman, 2017). Leon Battista Alberti documented the general polyalphabetic cipher in 1467 although this version did not switch encryption alphabets with each letter of plaintext (University of Babylon, 2011). Giovan Battista Bellaso is credited with another variant as early as 1564 (Bellaso, 1552).

Although Vigenère was considered unbreakable for some time (Simmons, 2009), it was cracked well before computers became available (Singh, 2001). Charles Babbage decrypted a letter enciphered in Vigenère in 1846 and later solved a double-enciphered message (Kahn, 1967). However, Babbage's work was not made public (Salomon, 2003). An officer in the Prussian army, Kasiski, published a method similar to Babbage's for breaking Vigenère in 1863 (Kahn, 1967). Nonetheless, the cipher was considered secure in the popular press as late as 1917 (The Oxford Math Center, 2018).

2.1. Taxonomy of Vigenère Ciphers

Given a cryptographic key, a cipher can change "plaintext" into "ciphertext" (*Figure 1*). The term "text" is used loosely to refer to any data. Ciphers may either use a single key for both



Figure 1: Ciphers transform plaintext into ciphertext and vice versa

encryption and decryption operations; or uses pairs of keys--one each for encryption and decryption. Symmetric ciphers reuse the same key for both encryption and decryption while asymmetric ciphers require a pair. Symmetric ciphers can use substitution or transposition cipher primitives to transform the data. Substitution ciphers replace characters in the plaintext to generate ciphertext. Examples include "s-boxes" in the Data Encryption Standard (DES) (Gargiulo, 2002) and rotors in the German Enigma machine (Rijmenants, 2016). Transposition only permutes the plaintext thus "shuffles the deck". Enigma plug boards (Rijmenants, 2016) and DES "p-boxes" (Forouzan, 2007) are examples of transposition. Vigenère only uses substitution.

2.1.1. Substitution Cipher Primitives

In simple substitution, the shift of the plaintext is consistent throughout the encryption process. The Caesar cipher with its key of 3 shifts each letter of plaintext forward three positions in the alphabet. "a" becomes "d", "b" becomes "e" and so forth. The alphabet forms a ring such that "x" loops back around to "a", "y" to "b", etc.¹. Another example using key = 1 is given (*Figure 2*).

Key:	11111 11111
Plaintext:	hello world
Ciphertext:	ifmmp xpsme

Figure 2: Using a key of 1, the phrase is encrypted by simple substitution

These ciphers can be broken using frequency analysis (Daniel Rodriguez-Clark, 2013). Since each character is shifted the same amount, the relative popularity of characters is preserved in the ciphertext. This is true for overall frequency and contextual frequency. Assuming an English alphabet encrypted with a Caesar cipher, "e" is statistically the most likely character of plaintext overall so "h" will tend to show up most frequently in the ciphertext. A cryptanalyst studying some ciphertext may assume the most popular ciphertext character translates to "e", the second most popular "t", third "a", and so on (Oxford Math Center, 2018). Context also matters. If position is preserved in the cipher text (i.e., spaces are not removed), then "t" is the most likely character to start a word (Oxford Math Center, 2018).

Also, if any ciphertext character is deciphered, then all other occurrences of that character are immediately known. In *Figure 2*, the letter "m" appears three times in the ciphertext. If any one of these is determined to be "l" (lowercase L), then all three are instantly recognized.

¹ An online substitution cipher tool is available at https://learncryptography.com/tools/caesarcipher

2.1.2. Polyalphabetic Cipher Primitives

Polyalphabetic ciphers like Vigenère improve upon simple substitution by using a multicharacter key. Polyalphabetic ciphers can be thought of as several simple substitution ciphers used in rotation. The length of the key determines how many characters of plaintext can be encrypted before the key must be reused. In the following example, the key "sans" is highlighted in alternating colors to show the application of the key².

Keyword (sans):	sans	sans	sai	ns <mark>sanssa</mark> r	IS	sanssans	sans	sanssans
Plaintext:	the	spy	is	driving	a	little	red	corvette
Ciphertext:	1hr	kpl	as	vjiiafg	s	lv111r	jeq	uoenwtgw

Figure 3: Example of polyalphabetic encryption with key "sans"

	Key Encoding											
a	b	С	d	е	f	g	h	i	j	k	l	т
0	1	2	3	4	5	6	7	8	9	10	11	12
3												
п	0	р	q	r	S	t	и	v	W	x	У	Ζ
13	14	15	16	17	18	19	20	21	22	23	24	25

Table 1: Key encoding used in example

In contrast to the previous "hello world" example (*Figure 2*), the plaintext in the next example is the same (*Figure 4*), but the five-character key is *12345*. Therefore, each of the first five characters of plaintext is shifted independently according to the key for that column. Because the key is five characters in length, it must be reused after the first five characters of plaintext. In this example, the key is reused for "world" (*Figure 4*).

² In this example, spaces are not encrypted for simplicity

Jeremy Druin, jdruin@gmail.com

Key:	12345 12345
Plaintext:	hello world
Ciphertext:	igopt xqupi

Figure 4: Using a key of 12345, the phrase is encrypted with polyalphabetic substitution

This method is more secure than the simple substitution cipher. In *Figure 2*, all characters including the three occurrences of "l" (lowercase L) were shifted the same amount. The polyalphabetic key *12345* in *Figure 4* shifts the first occurrence of "l" (lowercase L) to "o" (lowercase O) and the second occurrence to "p". This behavior reduces the chance that popular letters will form highly predictable patterns in the ciphertext. However, it is important to note that the second "l" (lowercase L) in "hello" was shifted 4 spots to "p" exactly the same as the "l" (lowercase L) in "world". This is a result of both letters being in the same position relative to the key; the fourth position. This coincidence foreshadows the Vigenère cipher's demise.

2.1.3. One-time pad

Assuming the cryptanalyst has only the ciphertext, there exists an unbreakable cipher. If a random polyalphabetic key at least as long as the plaintext is used only once, a cryptanalyst cannot recover the plaintext³ (RIJMENANTS, 2016). A cryptanalyst can discover some key that decrypts the ciphertext into an intelligible statement, but then find other keys that produce even more statements. There is no way to determine which message is correct since all are equally likely (RIJMENANTS, 2016).

It is theoretically possible to generate Vigenère cipher keys that fulfill the requirements of a one-time pad, but these may not be practical. Putting aside the issues of generating truly random keys, sharing keys securely and having enough key material, transporting the key itself becomes overwhelming. Recall the key must be at least as long as the plaintext. A mobile phone

³ If the cryptanalyst is allowed other forms of attack such as coercion of an adversary or collusion with a dishonest agent, the assumption does not hold.

Jeremy Druin, jdruin@gmail.com

alone generates about 4GB of traffic per month (Heuveldop, 2017). Imagine the problems if this amount is doubled by the use of one-time pad.

2.2. Software and Test Files

To encrypt, decrypt and analyze data using a variety of ciphers, python⁴ scripts are provided on GitHub in the "cryptography" repository⁵. The repository includes software needed to perform all operations and cryptanalysis demonstrated in this paper. Also, test files can be found in the "test-files" directory. The project includes scripts for many different ciphers and related utilities. Visionary.py and Freak.py are most applicable to this study.

2.2.1. Visionary.py

Script *visionary.py* encrypts/decrypts using a Vigenère cipher⁶. Unlike previous examples that were simplified for clarity, visionary.py works on all input bytes (i.e. a space character will be encrypted the same as any other). Character, binary and base64 input/output formats are supported. Input can be read from standard input⁷ or a file. Important arguments include the following.

-h,help	Show help	
-e,encrypt	Encrypt INPUT. This option	requires a KEY.
-d,decrypt	Decrypt INPUT. This option	requires a KEY.
-k KEY,key KEY	Encryption/Decryption key	
-v,verbose		Enables verbose output
-i INPUT_FILE,in	put-file INPUT_FILE	Read INPUT from an input file

These are some examples of usage⁸.

⁴ Python 3 is required and available at https://www.python.org/downloads/

⁵ https://github.com/webpwnized/cryptography

⁶ The original cipher used only characters in the alphabet for keys. visionary.py operates on bytes so values 0 - 255 are possible.

⁷ More information on standard input is available at

http://www.linuxdevcenter.com/pub/a/linux/lpt/13_01.html

⁸ Scripts were tested with Python 3.6.0 on Windows 10 version 1709, Python 3.6.4rc1 on Kali Linux 4.14.0 and Python 3.5.2 on Ubuntu 4.4.0

Encrypt the phrase "helloworld" with key 12345 (*Figure 5*)

python visionary.py --encrypt --key 12345 "helloworld"

```
C:\Users\Jeremy\Documents\GitHub\cryptography≻python visionary.py
--encrypt --key 12345 "helloworld"
igoptxqupi
```

Figure 5: Encrypt the phrase "helloworld" with key 12345

Decrypt the phrase "igoptxqupi" with key 12345 (Figure 6)

python visionary.py --decrypt --key 12345 "igoptxqupi"



Figure 6: Decrypt the phrase "igoptxqupi" with key 12345

Take input from binary file, encrypt, then redirect output to binary file (Figure 7)

python visionary.py --encrypt --key Password1 --input-format=binary --output-

format=binary --input-file=funny-cat-1.jpg > enc-funny-cat-1.bin

C:\Users\Jeremy\Documents\GitHub\cryptography\test-files>python ../visionary.py --encrypt --key Password1 --input-format=binary --output-format=binary --input-file=funny-cat-1.jpg > enc-funnycat-1.bin

Figure 7: Take input from binary file, encrypt, then redirect output to binary file

2.2.2. Freak.py

Freak.py is a utility that calculates statistics useful for analysis. The script supports character, binary and base64 input formats. Analysis is performed on each byte of input. Like visionary.py, input can be read from standard input⁹ or a file and four types of analysis are supported: histogram, statistics, index of coincidence and polyalphabetic columns (columnar)¹⁰.

A histogram is a graphical representation of the frequency of elements in a data set (Collins English Dictionary - Complete & Unabridged 10th Edition, 2010). Presented as a bar chart on a set of characters, the relative frequency of each character is denoted by the height of the bar.

The following options are helpful:

-c,show-count	Show count for each byte of input				
-p,show-percent	Show percent representation for each byte of input				
-m,show-histogram Show histogram for each byte of input					
-a,show-ascii	Show ASCII representation for each byte of input				
t TOP_FREQUENCIES,top-frequencies TOP_FREQUENCIES					
	Only display top X frequencies				

Generally, the most common switches used with the histogram feature are count, percentage, show-histogram and top-frequencies. The following example counts the occurrences of each byte-value in a file and creates a histogram to display relative popularity. Byte-values range from 0 (0X00) to 255 (0XFF). In the example below, byte value 0 is the most frequent character by a large margin so the respective bar is relatively longer.

Considering each byte in file funny-cat-1.jpg, show count, percent and histogram for top 10 most common bytes (sorted by popularity) (*Figure 8*)

python freak.py -cpm -v -t 10 -i funny-cat-1.jpg

⁹ More information on standard input is available at

http://www.linuxdevcenter.com/pub/a/linux/lpt/13_01.html

¹⁰ "Polyalphabetic columns" are discussed more once the relevance of the key length is established

C:\Use	ers\Jeremy	y\Docume	nts\GitHu	>\cryptography>python	freak.py	-cpm -v -	t 10 -i	test-files	\funny-cat-1.jpg
Analys	sis of In	put							
Byte:	0	394	(1.03%)	#######################################					
Byte:	204	220	(0.58%)	###########					
Byte:	212	220	(0.58%)	###########					
Byte:	50	217	(0.57%)	###########					
Byte:	1	212	(0.56%)	###########					
Byte:	16	211	(0.55%)	###########					
Byte:	220	211	(0.55%)	###########					
Byte:	89	200	(0.52%)	##########					
Byte:	196	200	(0.52%)	##########					
Byte:	44	196	(0.51%)	##########					

Figure 8: Considering each byte in file funny-cat-1.jpg, show count, percent and histogram for top 10 most common bytes (sorted by popularity)

Calculating statistics is intuitive since the names of the arguments align directly with their function.

-mean,show-mean	Show Arithmetic Mean (Average)
-median,show-median	Show Median
-mode,show-mode	Show Mode (Most popular byte)
-antimode,show-anti-mode	Show Anti-Mode (Least popular byte)
-variance,show-variance	Show Variance
-stddev,show-standard-deviation	Show Standard Deviation
-e,show-entropy	Show Shannon entropy
-stats,show-statistics	
	Show mean, median, mode, variance, standard d

Show mean, median, mode, variance, standard deviation and Shannon entropy for each byte of input

Generally, freak.py is used to compute all available statistics on a file. As with other operations, calculations are made with respect to byte-value. The script also calculates Shannon entropy with a range of 0.0 to 8.0. This value is a relative indicator of how random the data appears (Ueltschi, 2006). Data that is encrypted well should be reasonably indistinguishable from random data. A strong cipher produces an even histogram and very high entropy (Lawlor, 2013). The histogram, mode and entropy are correlated. For data to appear random, the popularity of

each byte must be the same (on average). This results in a flat histogram and high entropy (VandenBrink, 2016).

For each byte in file encrypted-funny-cat-1.jpg, show all statistics: mean, median, mode, anti-mode, variance, standard deviation, and Shannon entropy (*Figure 9*)

python freak.py --show-statistics --verbose -i funny-cat-1.jpg

```
C:\Users\Jeremy\Documents\GitHub\cryptography>python freak.py
--show-statistics --verbose -i test-files\funny-cat-1.jpg
Arithmetic Mean (Average): 123.53
Median (Middle element): 123
Mode (Most populous): 0 (Count: 394 Ratio: 2.64)
Anti-Mode (Least populous): 215 (Count: 95 Ratio: 0.64)
Variance: 5469.60
Standard Deviation: 73.96
Entropy: 7.98
```

Figure 9: For each byte in file encrypted-funny-cat-1.jpg, show all statistics: mean, median, mode, anti-mode, variance, standard deviation, and Shannon entropy

Index of Coincidence (IOC) indicates when bytes at a common offset are related. This statistical measure and related features of freak.py will be explained during the analysis of the key length. The IOC can be calculated using the -ioc, --show-ioc flag as seen in the following.

Determine the index of coincidence of file encrypted-funny-cat-1.jpg (Figure 10)

python freak.py -ioc --verbose --input-file=encrypted-funny-cat-1.bin

C:\Users\Jeremy\Documents\GitHub\cryptography>python freak.py -ioc						
-verboseinput-file=test-files\encrypted-funny-cat-1.jpg						
Byte Offset: 01 [1.09] ####################################						
Byte Offset: 02 [1.06] ####################################						
Byte Offset: 03 [1.03] ####################################						
Byte Offset: 04 [0.94] ####################################						
Byte Offset: 05 [1.00] ###################################						
Byte Offset: 06 [1.16] ####################################						
Byte Offset: 07 [0.87] ####################################						
Byte Offset: 08 [1.87] ####################################						
Byte Offset: 09 [0.96] ####################################						

Figure 10: Determine the index of coincidence of file encrypted-funny-cat-1.jpg

2.2.3. Test Files

Four JPEG files are supplied for demonstration¹¹. Three files are taken from photos of cats (Figures 11-13). The fourth is a bi-chromatic image of Twitter, Inc. logo Larry Bird¹² (Figure 14). The fourth image is provided as a counter-example. The cryptanalysis feature of freak.py does not perform well with images that are only 1-2 colors. Analysis will show the extreme lack of color variation throws off what is usually the most popular byte.

 ¹¹ https://github.com/webpwnized/cryptography/tree/master/test-files
 ¹² The small, blue bird ironically appears to have its name revealed in a tweet (https://twitter.com/rsarver/statuses/174205732776976385)

Jeremy Druin, jdruin@gmail.com

Cryptanalysis of the Vigenère Cipher | 1



Figure 11: funny-cat-1.jpg



Figure 12: funny-cat-2.jpg



Figure 13: funny-cat-3.jpg



Figure 14: twitter-bird.jpg

An encrypted copy of funny-cat-1.jpg is included with the other test files. This file will be used in remaining demonstrations that require an encrypted file. The command used to encrypt was the following. The password is intentionally obfuscated to allow the reader to attempt to learn the password using techniques presented¹³.

¹³ The command with clear text password is available at https://github.com/webpwnized/cryptography#visionary

Jeremy Druin, jdruin@gmail.com

python visionary.py --encrypt --key [password]--input-format=binary --outputformat=binary --input-file=test-files\funny-cat-1.jpg > test-files\encrypted-funny-cat-1.jpg

visionary.py encrypts by iterating over each byte of the plaintext. As it proceeds, plaintext bytes are shifted into ciphertext bytes. Because the cipher is polyalphabetic, the amount of shift varies from byte to byte according to the password. Each byte of the key is used in succession from left to right to determine the shift for the respective plaintext byte. When the key bytes are exhausted, the key bytes are reused starting at the left most key byte again (*Figure 15*).

def do_encrypt(pByte: int, pKey: int) -> int: #e(x) = (x + k) % n return (pByte + pKey) % MODULUS

def do_decrypt(pByte: int, pKey: int) -> int: #d(x) = (x - k) % n return (pByte - pKey) % MODULUS

Figure 15: Encryption function

To ensure the encryption process worked well, the file can be decrypted then compared to the original (*Figure 16*).

python visionary.py --decrypt --key [password] --input-format=binary --outputformat=binary --input-file=test-files\encrypted-funny-cat-1.jpg > test-files\decryptedfunny-cat-1.jpg

fc /B test-files\funny-cat-1.jpg test-files\decrypted-funny-cat-1.jpg^{14 15}

¹⁴ fc.exe is included with Windows. diff works well in Linux.

¹⁵ /B compares file in binary mode

C:\Users\Jeremy\Documents\GitHub\cryptography>python visionary.py -decrypt --key rocky329 --input-format=binary --output-format=binary --input-file=test-files\encrypted-funny-cat-1.jpg > test-files\decry pted-funny-cat-1.jpg C:\Users\Jeremy\Documents\GitHub\cryptography>python visionary.py -decrypt --key rocky329 --input-format=binary --output-format=binary --input-file=test-files\encrypted-funny-cat-1.jpg > test-files\decry pted-funny-cat-1.jpg C:\Users\Jeremy\Documents\GitHub\cryptography>fc /B test-files\funny -cat-1.jpg test-files\decrypted-funny-cat-1.jpg Comparing files TEST-FILES\funny-cat-1.jpg and TEST-FILES\DECRYPTED-FUNNY-CAT-1.JPG FC: no differences encountered

Figure 16: To ensure the encryption process worked well, the file can be decrypted then compared to the original

2.3. A possible cryptanalysis of Vigenère cipher

2.3.1. An aside: Traffic Analysis

Before cryptanalysis can take place, reconnaissance is necessary to determine what has been encrypted. Context such as the original file format, the cipher used and other information is needed to attack the encryption (or perhaps to know a cryptanalysis attack is not likely to work). The communication patterns between systems can provide this background (Northcutt, 2007). Traffic Analysis seeks to answer questions such as "What encoding and encryption is usually used?", "What language is spoken?" and "What type of file is being transferred?". These and other conversational metrics may reveal the file type and encryption in play.

2.3.2. Potentially Useful Statistics: Unencrypted JPEG Files

JPEG is a binary format (Hamilton, 1992). Byte-values range from 0 (0X00) to 255 (0xFF). If JPEG files contain no distinguishing characteristics with respect to frequency of byte-values, the expected value of the mean and median is 127.5. All byte-values would be the mode¹⁶ and the Shannon Entropy would be 8.0. A series of statistics can be run on the test files to see if

¹⁶ Mode: Most popular value in a set

the byte values of JPEG files tend to have a prominent characteristic. freak.py is able to calculate mean, median, mode, standard deviation and entropy on the top 10 most popular bytes. The command is demonstrated here for file funny-cat-1.jpg and the same is run on the other three test files to generate the statistics. The results are summarized in *Table 2*.

Analys	sis of Inpu	ut		
Byte:	0 394	(1.03%)	#######	**********
Byte:	204	220	(0.58%)	############
Byte:	212	220	(0.58%)	###########
Byte:	50	217	(0.57%)	###########
Byte:	1 212	(0.56%)	#######	####
Byte:	16	211	(0.55%)	###########
Byte:	220	211	(0.55%)	###########
Byte:	89	200	(0.52%)	##########
Byte:	196	200	(0.52%)	##########
Byte:	44	196	(0.51%)	##########
Arithr	netic Mean	(Average	e): 123.9	53
Mediar	n (Middle e	element)	: 123	
Mode	(Most popul	Lus): 0		
- I				
Standa	ard Deviati	ton: 73.9	90	
Entro	7 00			
Entrop	py: 7.98			

python freak.py -cpme -mean -median -mode -stddev -t 10 -v -i funny-cat-1.jpg

Figure 17: Statistics for funny-cat-1.jpg

python freak.py -cpme -mean -median -mode -stddev -t 10 -v -i funny-cat-2.jpg

```
Analysis of Input
Byte: 0 88
           Byte: 45
           62
                 Byte: 21
           39
                 (0.78%) #################
           (0.74%) ################
Byte: 1 37
Byte: 26
           36
                 Byte: 43
           36
                 Byte: 16
           33
                 (0.66%) ################
Byte: 114
           33
                 Byte: 49
           32
                 Byte: 51
           32
                 (0.64%) ##############
Arithmetic Mean (Average): 119.68
Median (Middle element): 117.5
Mode (Most populus): 0
Standard Deviation: 75.11
Entropy: 7.91
```

Figure 18: Statistics for funny-cat-2.jpg

python freak.py -cpme -mean -median -mode -stddev -t 10 -v -i funny-cat-3.jpg

```
Analysis of Input
Byte: 0 96
          Byte: 45
            63
                   Byte: 1 51
Byte: 46
            42
                   (0.70%) ###############
Byte: 23
            40
                   (0.67%)
                         ##############
            40
Byte: 146
                   (0.67%) ################
            40
Byte: 150
                   (0.67%) ################
            39
Byte: 92
                   (0.65%) ###############
            Byte: 2 38
Byte: 70
                   (0.63%) ##############
            38
Arithmetic Mean (Average): 121.92
Median (Middle element): 120.5
Mode (Most populus): 0
Standard Deviation: 74.81
Entropy: 7.93
```

Figure 19: Statistics for funny-cat-3.jpg

python freak.py -cpme -mean -median -mode -stddev -t 10 -v -i twitter-bird.jpg

Analy	usic of Inn	+			
Analy	SIS OT INP	ut 2220	(8 67%) ####################################		
Byte:	32	2220 #########	(8.03 <i>%</i>) ####################################		***************************************
######		(7 7 7 6 %)	****		
вусе: ##	0 1995	(7.76%)		"Analysis of Inp	ut
Byte:	255	338	(1.31%) ####################################	#Puto: 22	2220 (0 62%)
Byte:	12	273	(1.06%) ####################################	byte. 52	2220 (0.03%)
Byte:	73	259	(1.01%) ####################################	**************	***********
Byte:	1 251	(0.98%)	*****		
Byte:	98	247	(0.96%) ####################################	Bvte: 0 1995	(7.76%) ########
Byte:	116	241	(0.94%) ####################################	-,	(1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Byte:	111	238	(0.93%) ####################################		
Byte:	118	238	(0.93%) ####################################	Arithmetic Mean	(Average): 105.24
Arith	nmetic Mean	(Averag	e): 105.24		
Media	an (Middle	element)	: 98	Median (Middle e	lement): 98
Mode	(Most popu	lus): 32			\
Stand	lard Deviat	ion: 78.	40	Mode (Most popul	us): 32
Entro	opy: 7.30			-Standard Doviati	on: 79 40
				Stanuard Deviati	011. 70.40
				Entrony: 7 30	
				Encropy: 7.50	

Figure 20: Statistics for twitter-bird.jpg

	Funny Cat 1	Funny Cat 2	Funny Cat 3	Larry Bird
Mean	123.53	119.68	121.92	105.24
Median	123	117.5	120.5	98
Mode	0	0	0	32
Standard	73.96	75.11	74.81	78.40
Deviation				
Entropy	7.98	7.91	7.93	7.30

Table 2: Statistics for test files

The figures show a byte-value of 0 is pronounced in all of the JPEG except Larry Bird. However, even in this counter-example, byte-value 0 makes up 7.76% of the file. This is well

above the 0.39% expected if there were no prominent byte-values¹⁷. Also, even though bytevalue 0X32 was the mode at 8.63%, byte-value 0 was a close second (*Figure 20*).

2.3.3. Potentially Useful Statistics: JPEG Files Encrypted with Vigenère

The same statistics can be run on the encrypted version of funny-cat-1.jpg, then the results compared against those in *Figure 17* and *Table 2 - Funny Cat 1*. The command to calculate the data is the following.

python freak.py -cpme -mean -median -mode -stddev -t 10 -v -i encrypted-funny-cat-1.jpg

Byte:	216	203	(0.53%)	###########	more even
Byte: Byte: Byte:	24 12 49	199 187 187	(0.32%) (0.49%) (0.49%)	*********** *********** *****	in unencrypte
Byte: Byte:	4 25	186 185	(0.49%) (0.49%)	*****	inc
Byte: Byte: Byte:	164 41 16	185 184 181	(0.49%) (0.48%) (0.47%)	########## ########### #############	
Byte:	3	179	(0.47%)	****	
Fi	igure 21: Stat	istics of enc	erypted-fun	ny-cat-1.jpg	

Figure 21: Statistics of encrypted-funny-cat-1.jpg

¹⁷ Assuming all bytes are equally likely, any randomly chosen byte should be present about 1 / 256 * 100 = 0.39% of the time.

Jeremy Druin, jdruin@gmail.com

	funny-o	at-1.jpg	encrypted-funny-cat-1.jpg		
Mean	123.53		125.14		
Median	123		124		
Mode	0		216		
Mode Count (Ratio)	394 (2.64)		203 (1.36)		
Anti-Mode	215 } 2.00		188	}0.57	
Anti-Mode (Ratio)	95 (0.64)		117 (0.79)		
Standard Deviation	73.96		73.96		
Entropy	7.98		7.99		

Figure 22: Comparison between encrypted and unencrypted JPEG (Vigenère encryption)

Vigenère has suppressed some of the identifying characteristics of the JPEG file, but the mean and median are still off the expected value of is 127.5 for a well encrypted JPEG. Vigenère flattened the histogram by spreading out the popular bytes more evenly over the range. This is also observed in the difference in the count of bytes that make up the mode and anti-mode¹⁸. The mode count ratio is the number of bytes for the mode divided by the number of bytes expected for a random distribution. For funny-cat-1.jpg, the mode count ratio is 2.64 which says there are more than 2.5 times as many "0" than expected if the distribution of byte-values were perfectly even. Vigenère reduces the magnitude of the mode and the anti-mode as it distributes these extremes over the rest of the range. As a result, the difference between mode and anti-mode ratios shrinks from 2.00 to 0.57. However, Vigenère does not transform the JPEG file into one that appears to be made of random bytes. There is still a prominent mode suggesting the Vigenère cipher can be broken.

2.4. Cryptanalysis of Vigenère-encrypted JPEG files

¹⁸ Anti-mode: Least popular byte

Jeremy Druin, jdruin@gmail.com

Recall a Vigenère cipher is effectively a series of substitution ciphers. Using a key length of 5 as an example (*Figure 23*), the first byte of the key is used to encrypt both plaintext character 1 and 6 because the key must be reused. This pattern holds for the other bytes in the key. In *Figure 24*, the ciphertext is arranged so characters encrypted with the same key byte are aligned in columns. Each of these columns is a substitution cipher encrypted by the respective key byte a.k.a. the "column key".

Key:	12345	12345
Plaintext:	hello	world
Ciphertext:	ig opt	xqu pi

Figure 23: Example encryption with Vigenère



Figure 24: Ciphertext arranged into columns under the key byte used to encrypt those respective characters

Substitution ciphers can be broken using frequency analysis (Lyons, 2012). In this technique, the most popular character in the ciphertext is identified. If the mode of the ciphertext is calculated, the value is probably the most popular letter in the plaintext encrypted with the key. Since the encrypted byte and the plaintext byte are known, the key can be recovered by adjusting the ciphertext by the value of the plaintext. The result will be the key most of the time.

Ciphertext created by Vigenère ciphers can be rearranged so that the columns form substitution ciphers (*Figure 24*). For any given column of ciphertext, the mode can be found. Statistical analysis showed JPEG files tend to have byte 0 as mode in the plaintext. Therefore,

the mode of the ciphertext is likely the key for that column¹⁹. However, in order to arrange the ciphertext bytes into columns with respect to the key byte that encrypted that column, the key-length must be known.

2.4.1. Index of Coincidence

The value of a character of ciphertext is determined by two inputs: the value of the plaintext and the column key. For example, the first character of ciphertext in *Figure 25* is "i" because the first plaintext character "h" was shifted one letter by the key "1". The last character of ciphertext is also "i" but was generated when plaintext character "d" was shifted 5 spots by key "5".

Key:	12345	12345
Plaintext:	hello	world
Ciphertext:	igopt	xqu pi

Figure 25: Example encryption with Vigenère

Note there are also two characters with value "p" in the ciphertext (*Figure 25*). These characters were both generated from plaintext character "l" (lowercase L) shifted 4 positions. In the former case of ciphertext letter "i", the key value was different but, in this latter, the key value was the same. The probability of getting these "doubles" is greatly influenced if the key used to encrypt the characters is identical.

Some plaintext letters are more popular than others. For example, the chance of randomly choosing the letter "e" out of a text is about 12% (Cornell University, 2004). Without encryption, the chance of choosing two letter "e" is 1.44%²⁰. When encrypted with Vigenère, those two letter "e" would not necessarily be encrypted with the same key. This would only happen if the key value in the respective key positions happened to be the same. The chances of hitting doubles is

¹⁹ Normally the column key is calculated by subtracting the mode of the plaintext from the ciphertext, but the mode of the plaintext happens to be 0, so no adjustment is needed. ²⁰ 12% * 12%

lessened since popular letters only have about a 1/(key-length) chance of being encrypted by the same value²¹.

When the ciphertext characters are in the same position with respect to the key, the probability of the key is not relevant. Plaintext letters from the same "column" (*Figure 24*) are guaranteed to be shifted the same amount. To get doubles for two ciphertext characters from the same column, it only matters that the same plaintext letters were encrypted. Popular letters regain their influence. Getting doubles is easier when observing two ciphertext characters from the same column (*Figure 26*).



Figure 26: Ciphertext arranged into columns under the key byte used to encrypt those respective characters

Imagine ciphertext is arranged in columns such that all characters in the respective column are encrypted with the same key-value (*Figure 26*). The chance of drawing doubles from two different columns is about $0.038 (3.8\%)^{22}$. However, if values are picked within the same column, the chance is almost twice as good at 0.065 (6.5%) (Christensen, 2015). If we check for doubles every other character, then every third character, then every fourth character, etc., the chance of getting doubles will spike once the spacing or "index" is aligned with the key length. This *index of coincidence (IOC)* is calculated with the following formula (*Figure 27*).

²¹ "About" because the key itself might have duplicate letters

²² Presuming a "sufficiently long key" or "as the key length goes to infinity"

$$\mathbf{IC} = rac{\displaystyle\sum_{j=1}^{N} [a_j = b_j]}{\displaystyle N/c},$$

Figure 27: Formula for Index of Coincidence (Wikipedia, 2017)

One method to determine IOC is to make a copy of the ciphertext under itself (*Figure 28*). The ciphertext is shifted one position and the index of coincidence is calculated. Then the IOC is recalculated after shifting two positions. This process continues until number of shifts exceeds the length of the key. An educated guess of key length can be made from traffic analysis or reconnaissance. Alternatively, since computers can automate the calculations, brute-force of several dozen shifts could provide enough coverage²³. There is no penalty for trying too many shifts. The value of the IOC spikes each time the index is a multiple of the key length.



Figure 28: Checking for doubles after shifting ciphertext 1,2,3,... positions

For the phrase "hello world" encrypted with key 12345, the IOC would tend to be maximal when the amount of shift was a multiple of 5. The freak.py script can be used to examine encrypted-funny-cat-1.jpg.

python freak.py -ioc -i encrypted-funny-cat-1.jpg

²³ freak.py has MAX_SHIFTS_TO_ANALYZE = 50 by default. This constant can be changed in function get_kappa_index_of_coincidence().

C:\Users\Jeremy\Documents\GitHub\cryptography>python Freak.py -ioc -i test-files\encrypted-funny-cat-1.jpg	g
91 [1.12] ####################################	
92 [1.12] ####################################	
03 [0.93] ####################################	
94 [1.38] ####################################	
95 [1.10] ####################################	
96 [1.11] ##################################	
07 [0.89] #################	
08 [1.87] ####################################	
99 [0.99] ###################################	
L0 [1.05] ####################################	
L1 [1.09] ####################################	
L2 [1.13] ####################################	
L3 [1.13] ####################################	
L4 [1.03] ####################################	
L6 [1.50] ####################################	
17 [0.92] #################	
19 F1 021 ++++++++++++++++++++++++++++++++++	

Figure 29: IOC calculation for shifts 1 - 49

For funny-cat-1, spikes in the value of IOC found at shifts 8,16, 24, etc. indicate the key length is 8 (*Figure 29*).

2.4.2. Key recovery

Since the key length is known, the ciphertext can be broken into blocks of 8 characters so that characters encrypted with the same key byte are aligned in columns (*Figure 30*).

	K	ey Len	gth = 8			Ke	y Length	= 8		etc
115 149	96 169 117 85	233 112	205 21 55 121	149 26 3 13 9 214	147 54 4 162	42 176 220 1 1	5 15 17 .92 93	7 118 40 47	210 18 69 1 199 233	147 99 107
Key	Byte:	1	2	3	4	5	6	7	8	
Each col	umn of 🦯	115	96	169	233	205	21	149	26	
bytes er	ncrypted	147	54	42	176	15	177	118	210	
with sar	ne key	18	69	147	149	117	85	112	55	
		121	13	9	214	162	220	1	192	
		93	40	47	1	199	233	99	107	

Figure 30: Ciphertext from encrypted-funny-cat-1.jpg in rows of 8 bytes

The key byte for each column can be recovered using techniques prescribed for a substitution cipher. Prior analysis shows the most popular byte in the plaintext probably has a value of zero. Therefore, the mode of each column should be the value of the key byte²⁴. The entire key is recovered by repeating this process for each column. The "-g" causes freak.py to guess the key bytes. "-col 8" provides the length of the key (*Figure 31*).

python freak.py -c -g -t 1 -col 8 --input-file=encrypted-funny-cat-1.jpg

```
C:\Users\Jeremy\Documents\GitHub\cryptography>python freak.py -c
-g -t 1 -col 8 --input-file=test-files\encrypted-funny-cat-1.jpg
Analysis of Column 1
Analysis of Input
                Lowercase: r
                                Uppercase: R
                                                 Numeric: A
Best guess
17
        58
Analysis of Column 2
Analysis of Input
                                Uppercase: 0
                                                 Numeric: >
Best guess
                Lowercase: o
14
        36
Analysis of Column 3
Analysis of Input
Best guess
                Lowercase: c
                                Uppercase: C
                                                 Numeric: 2
        45
Analysis of Column
```

Figure 31: Output of "guess" feature of freak.py

²⁴ Referring to *Figure 15*, the formula to encrypt the plaintext byte is "value of plaintext byte" + "value of key byte". Since the "value of plaintext byte" is 0 for the most popular bytes, the most popular ciphertext bytes are probably the value of the key.

Cryptanalysis of the Vigenère Cipher | 2

guess	Lowercase:	r	Uppercase:	R	Numeric:	А
guess	Lowercase:	0	Uppercase:	0	Numeric:	>
guess	Lowercase:	С	Uppercase:	С	Numeric:	2
guess	Lowercase:	k	Uppercase:	K	Numeric:	:
guess	Lowercase:	У	Uppercase:	Y	Numeric:	Η
guess	Lowercase:	d	Uppercase:	D	Numeric:	3
guess	Lowercase:	С	Uppercase:	С	Numeric:	2
guess	Lowercase:	j	Uppercase:	J	Numeric:	9
	guess guess guess guess guess guess guess guess	guessLowercase:guessLowercase:guessLowercase:guessLowercase:guessLowercase:guessLowercase:guessLowercase:guessLowercase:guessLowercase:	guessLowercase:rguessLowercase:oguessLowercase:cguessLowercase:kguessLowercase:yguessLowercase:dguessLowercase:cguessLowercase:cguessLowercase:cguessLowercase:c	guessLowercase:rUppercase:guessLowercase:oUppercase:guessLowercase:cUppercase:guessLowercase:kUppercase:guessLowercase:yUppercase:guessLowercase:dUppercase:guessLowercase:cUppercase:guessLowercase:cUppercase:guessLowercase:cUppercase:guessLowercase:cUppercase:guessLowercase:jUppercase:	guessLowercase: rUppercase: RguessLowercase: oUppercase: OguessLowercase: cUppercase: CguessLowercase: kUppercase: KguessLowercase: yUppercase: YguessLowercase: dUppercase: DguessLowercase: cUppercase: CguessLowercase: cUppercase: DguessLowercase: cUppercase: CguessLowercase: jUppercase: J	guessLowercase: rUppercase: RNumeric:guessLowercase: oUppercase: ONumeric:guessLowercase: cUppercase: CNumeric:guessLowercase: kUppercase: KNumeric:guessLowercase: yUppercase: YNumeric:guessLowercase: dUppercase: DNumeric:guessLowercase: cUppercase: DNumeric:guessLowercase: cUppercase: CNumeric:guessLowercase: cUppercase: CNumeric:guessLowercase: jUppercase: JNumeric:

Figure 32: Output of freak.py "guess" with extraneous lines removed

Because visionary.py normalizes the key bytes before encryption, information about whether the key phrase was uppercase, lowercase or numeric is lost²⁵. freak.py displays all three possibilities (*Figure 32*). "Rocky329", "ROCKY329" and "rocky329" are reasonable guesses. Trying "rocky329" successfully decrypts the plaintext²⁶.

2.5. Opportunities for Improvement

JPEG files were specifically chosen for demonstration because the pronounced mode makes for easier analysis. To cryptanalyze English text, frequency analysis can be used (K.W. Lee, 2006) but freak.py does not implement these techniques. A modular implementation that uses character frequencies based on the language would allow languages besides English to be supported.

The image of the Twitter, Inc. logo showed that redundant color schemes can cause the mode of a JPEG file to be a value other than 0x00. freak.py might be improved in this respect in a couple of ways. If the script used the top three most popular bytes, the user could see which outputs reasonable guesses. Alternatively, the user could be allowed to enter which byte they prefer based on the results of the statistical analysis. Finally, the program could run the statistical analysis itself then automatically use the mode found.

²⁵ Reference function do_derive_key() in visionary.py

²⁶ For implementations of Vigenère that do not normalize the key, freak.py would simply output the password. Even though visionary.py makes analysis more difficult, the author stayed with the implementation because it mimics a cipher encountered in "real life".

Other tools already possess some enhanced features. FeatherDuster²⁷ by Daniel Crowley can automate much of this process for multiple types of ciphers (Crowley, 2016). The pythonbased tool can detect weak ciphers and improper use of cryptographic mechanisms. It includes code breaking features. FeatherDuster can analyze ciphertext, recommend an attack module or try all attacks with "autopwn"²⁸.

3. Conclusion

Vigenère cipher makes a good starting point to learn about cryptography and cryptanalysis. Vigenère gives an opportunity to explore substitution ciphers, polyalphabetic ciphers and multiple statistical techniques. The study shows some components of cryptanalysis: traffic analysis, identification of encrypted data, an introduction to applying statistics and an opportunity to write helpful scripts. Vigenère is a classical cipher. Defeating the cipher is not a gateway into professional code-breaking but gives the amateur insight into the subject of cryptanalysis.

For security professionals who do not specialize in cryptography, an introduction to cryptanalysis provides an appreciation for the important subject and highlights a valuable lesson. Cryptanalysis can be difficult even for a centuries-old, obsolete cipher. It is that much harder for modern ciphers. Failure to envision a way to break a cipher does not prove the cipher is invincible (Schneier, 2011). To have confidence in an encryption system, it is important to use proven ciphers that have been targeted by multiple, competent cryptanalysts over a significant period of time.

²⁷ https://github.com/nccgroup/featherduster

²⁸ According to http://schd.ws/hosted_files/issw2016/a6/Cryptanalib_and_FeatherDuster.pdf, a hat tip to Metasploit.

Jeremy Druin, jdruin@gmail.com

Bellaso, GB. (1552, 12 22). La cifra nuovamente da lui ridotta a grandissima brevita etc.
Retrieved from Google Play Books:
https://play.google.com/store/books/details/Giovan_Battista_Bellaso_La_cifra_nuovam
ente_da_lui?id=GbZRAAAAcAAJ
Christensen, C. (2015). Cryptanalysis of the Vigenère Cipher: The Friedman Test. Retrieved from
NKU: https://www.nku.edu/~christensen/1402%20Friedman%20test%202.pdf
Collins English Dictionary - Complete & Unabridged 10th Edition. (2010). histogram. Retrieved
from Dictionary.com: http://www.dictionary.com/browse/histogram
Collins English Dictionary. (2012). Cryptanlysis. Retrieved from Collins English Dictionary -
Complete & Unabridged 10th Edition: http://www.dictionary.com/browse/cryptanalysis
Cornell University. (2004). English Letter Frequency (based on a sample of 40,000 words).
Retrieved from Cornell University: https://www.math.cornell.edu/~mec/2003-
2004/cryptography/subs/frequencies.html
Crowley, D. ". (2016). Cleaning up Magical Crypto Fairy Dust with Cryptanalib and
FeatherDuster. Retrieved from SCHED:
http://schd.ws/hosted_files/issw2016/a6/Cryptanalib_and_FeatherDuster.pdf
Crypto Museum. (2015, 8 28). One-Time Pad. Retrieved from Crypto Museum:
http://cryptomuseum.com/crypto/otp/index.htm
Daniel Rodriguez-Clark. (2013). Frequency Analysis. Retrieved from Crypto Corner:
http://crypto.interactive-maths.com/frequency-analysis-breaking-the-code.html
Forouzan, B. A. (2007, 2 28). Data Encryption Standard (DES). Retrieved from Cryptography and
Network Security:
http://highered.mheducation.com/sites/dl/free/007070208x/877405/Chapter_06_Data
_Encription_Standard.pdf
Gargiulo, J. (2002, 7 25). S-Box Modifications and Their Effect in DES-like Encryption Systems.
Retrieved from SANS Institute InfoSec Reading Room: https://www.sans.org/reading-
room/whitepapers/vpns/s-box-modifications-effect-des-like-encryption-systems-768
Hamilton, E. (1992, 9 1). JPEG File Interchange Format. Retrieved from W3.org:
https://www.w3.org/Graphics/JPEG/jfif3.pdf
Heuveldop, N. (2017, 6 1). Ericsson Mobility Report. Retrieved from Ericsson:
https://www.ericsson.com/assets/local/mobility-report/documents/2017/ericsson-
mobility-report-june-2017.pdf
Jeremy Norman. (2017, 10 22). Blaise de Vigenère Describes What is Later Known as the
Vigenère Cipher. Retrieved from HistoryofInformation.com:
http://www.historyofinformation.com/expanded.php?id=2011
K.W. Lee, C. T. (2006). Semantic Scholar. Retrieved from DECRYPTING ENGLISH TEXT USING
ENHANCED FREQUENCY ANALYSIS:
https://pdfs.semanticscholar.org/5013/213db36162f6e5ae6d2f1c72fe8240adb567.pdf
Kahn, D. (1967). The Codebreakers. New York: Macmillian.
Lawlor, D. O. (2013). Information Theory, Entropy, and Key Strength. Retrieved from CS 463
Lecture: https://www.cs.uaf.edu/2013/spring/cs463/lecture/01_25_entropy.html

Lyons, J. (2012). *Simple Substitution Cipher*. Retrieved from Practical Cryptography: http://practicalcryptography.com/ciphers/simple-substitution-cipher/

Math Explorers Club. (2003, 3 8). *Polyalphabetic Substitution Ciphers*. Retrieved from Cornell University: https://www.math.cornell.edu/~mec/2003-2004/cryptography/polyalpha/polyalpha.html

Merriam-Webster. (2017, 12 3). *Cryptography*. Retrieved from Merriam-Webster: https://www.merriam-webster.com/dictionary/cryptography

- Northcutt, S. (2007, 5 16). *Traffic Analysis*. Retrieved from SANS: https://www.sans.edu/cyber-research/security-laboratory/article/traffic-analysis
- NOVER, H. (2004). ALGEBRAIC CRYPTANALYSIS OF AES: AN OVERVIEW. Retrieved from semanticscholar.org:

https://pdfs.semanticscholar.org/9924/59258de4ff113e84e1813a53e3bad96fcc1a.pdf

- Oxford Math Center. (2018). Letter Frequencies in English. Retrieved from Oxford Math Center: http://www.oxfordmathcenter.com/drupal7/node/353
- Rijmenants, D. (2016). *CIPHER MACHINES AND CRYPTOLOGY*. Retrieved from Technical Details of the Enigma Machine:

http://users.telenet.be/d.rijmenants/en/enigmatech.htm#plugboard

Rijmenants, D. (2016). *Technical Details of the Enigma Machine*. Retrieved from CIPHER MACHINES AND CRYPTOLOGY:

http://users.telenet.be/d.rijmenants/en/enigmatech.htm#rotorencryption

RIJMENANTS, D. (2016, 1 22). THE COMPLETE GUIDE TO SECURE COMMUNICATIONS WITH THE ONE TIME PAD CIPHER. Retrieved from users.telenet.be:

http://users.telenet.be/d.rijmenants/papers/one_time_pad.pdf

Salomon, D. (2003). *Data Privacy and Security: Encryption and Information Hiding*. Springer Science & Business Media.

Schneier, B. (2011, 4 15). "Schneier's Law". Retrieved from Schneier on Security: https://www.schneier.com/blog/archives/2011/04/schneiers_law.html

- Simmons, G. J. (2009, 6 22). *Substitution cipher*. Retrieved from Encyclopedia Britannica: https://www.britannica.com/topic/substitution-cipher
- Simmons, G. J. (2009, 7 22). *Vigenère cipher*. Retrieved from Encyclopædia Britannica: https://www.britannica.com/topic/Vigenere-cipher

Singh, S. (2001). The Code Book. New York, New York: Delacorte Press.

- The Oxford Math Center. (2018). *The Vigenere Cipher*. Retrieved from The Oxford Math Center: http://www.oxfordmathcenter.com/drupal7/node/169
- Ueltschi, D. (2006). *Introduction to Statistical Mechanics*. Retrieved from http://www.ueltschi.org: http://www.ueltschi.org/teaching/chapShannon.pdf
- University of Babylon. (2011). *Vigenère cipher*. Retrieved from University of Babylon:
- http://www.uobabylon.edu.iq/eprints/paper_11_1363_649.pdf
- University of Rhode Island. (2013). *Classical Cryptography*. Retrieved from University of Rhode Island: https://www.cs.uri.edu/cryptography/classicalsubstitution.htm
- University of Rhode Island. (2013). *Classical Cryptography.* Retrieved from University of Rhode Island: https://www.cs.uri.edu/cryptography/classicalvigenere.htm

- VandenBrink, R. (2016, 8 8). SANS ISC InfoSec Forums. Retrieved from Internet Storm Center: .e. Jpy+t. .coincidence https://isc.sans.edu/forums/diary/Using+File+Entropy+to+Identify+Ransomwared+Files/