



Global Information Assurance Certification Paper

Copyright SANS Institute
Author Retains Full Rights

This paper is taken from the GIAC directory of certified professionals. Reposting is not permitted without express written permission.

Interested in learning more?

Check out the list of upcoming events offering
"Security Essentials Bootcamp Style (Security 401)"
at <http://www.giac.org/registration/gsec>

Black ICE 2.5 Events, False Positives and Custom Attack Signatures

Alan Mercer, GSEC Practical Version 1.2f

Introduction

The major challenge for administrators of Intrusion Detection Systems is distinguishing between events that are genuine malicious activity and those that are false positives.

This paper aims to help BlackICE IDS administrators by identifying and classifying some events frequently seen by IDS agents in two common deployments – on a DMZ web server and on systems within an internal (mainly Microsoft) network.

Network ICE do provide BlackICE event ('intrusion') descriptions in an online database [1], but many of these need further research before they can be classified satisfactorily. This paper includes additional research into some common events.

The nature of BlackICE's detection engine means that certain generic events may be triggered by different attacks (e.g. the **HTTP field with binary** event). IDS administrators are encouraged to further research all reported events thoroughly and to not assume event X is a result of attack Y.

The last section of the paper covers an unsupported method of creating custom BlackICE attack signatures that may prove useful in certain circumstances. A custom attack signature could be used to detect a new attack in the period between the attack being first identified and the vendor releasing an official attack signature update.

Please note that an in-depth discussion of incident handling and response procedures is not part of this research. Other papers available from SANS [2] address such issues.

BlackICE IDS Agent Configurations

These investigations were made using the Enterprise edition (version 2.5) of Network ICE's BlackICE product and not BlackICE Defender, the personal IDS and firewall. However certain sections are relevant, particularly the custom attack signature definition.

The Agents used in this research were host-based BlackICE Agent for Server 2.5ev and BlackICE Agent for Workstation 2.5ev running on Windows NT/2000. Both agents were reporting to an ICEcap console version 2.5eq. The network-based BlackICE Sentry agent was not used, though a Sentry agent will generate identical events when monitoring passing network traffic.

The Server agents were installed on Internet-facing DMZ IIS web servers offering both web and FTP services. The only traffic allowed into the DMZ from the Internet was on port 80 (Web), port 443 (Secure Web) and port 21 (FTP) to all machines.

Machines on the internal network were running both Server and Workstation agents.

Common BlackICE events generated by Internet-facing IIS web servers agents

As soon as Internet-facing web servers are connected to the Internet they will bombard the IDS administrator with events to investigate and classify.

With only ports 21, 80 and 443 open most of the malicious activity will fall into 3 categories: web-based server attacks (e.g. Nimda worm, Code Red and IIS Printer buffer overflows), FTP activity and Operating System (O/S) fingerprinting attempts.

It is worth noting that if the IDS agents pick up activity on any ports other than ports 21, 80 and 443 it points to a misconfiguration of the firewall. For example some firewalls allow inbound/outbound DNS traffic to pass by default [3].

Note also that Workstation agent event descriptions are simpler than Server agent event descriptions. Certain Workstation agent events may have generic descriptions like **HTTP Attack**.

Code Red Worm

The Code Red [4] worm hit the Internet around July 19th 2001 and after massive initial activity Code Red incidents have fallen away. Server agents report the following events when hit by various flavours of Code Red attack.

Original Code Red

ISAPI Extension Overflow

Parameters:
length: 362
URL: /default.ida
arg: NNNNNNNN (cont.)

Code Red II (& Variants)

ISAPI Extension Overflow

Parameters:
length: 362
URL: /default.ida
arg: XXXXXXXX (cont.)

eEye Code Red scan [5]

ISAPI Extension Overflow

Parameters:
length: 222
URL: /x.ida
arg: AAAAA (cont.)

Though it is rarer to see Code Red II events anymore, attacks from Code Red still persist and will continue to do so for some time [6]. Note that unlike Nimda, Code Red attacks only trigger one BlackICE event per attack.

Nimda Worm (and variants)

As Code Red activity started to subside a new and highly infectious worm, known as Nimda [7], struck the Internet around the 17th September 2001. From a very high initial attack rate, attack numbers have fallen, though Nimda-infected machines still account for a large proportion of incoming attacks

Black ICE agents report a number of events in response to Nimda attack. These events are generally triggered in batches of 4 from the same IP address over a 1-second interval. Repeated attack is common.

HTTP UTF8 backtick

Parameters:

URL: = /scripts/../../../../winnt/system32/cmd.exe |
/scripts/../../../../winnt/system32/cmd.exe

HTTP URL with double encoded ../

Parameters:

URL: = /_mem_bin/../../../../winnt/system32/cmd.exe |
/_vti_bin/../../../../winnt/system32/cmd.exe |
/msadc/../../../../V...../...../...../winnt/system32/cmd.exe |
/scripts/../../../../winnt/system32/cmd.exe

HTTP URL Scan

Parameters:

URL: = /_mem_bin/../../../../winnt/system32/cmd.exe |
/_vti_bin/../../../../winnt/system32/cmd.exe |
/c/winnt/system32/cmd.exe | /d/winnt/system32/cmd.exe

IIS System 32 Command

Parameters:

URL: = /_mem_bin/../../../../winnt/system32/cmd.exe |
/_vti_bin/../../../../winnt/system32/cmd.exe |
/c/winnt/system32/cmd.exe | /d/winnt/system32/cmd.exe |
/msadc/../../../../V...../...../...../winnt/system32/cmd.exe

Note these events are generic and can be triggered by attacks other than the Nimda worm.

IIS 5.0 Printer Buffer Overflow Attack

Seen less frequently are attempts to exploit an IIS 5.0 buffer-overflow reported in May 2001 [8]. Like Nimda, these IIS printer buffer overflow attacks trigger more than one event. The event pairs, generated from 1 IP address at the same time, are

IIS .printer overflow

Parameters:

length = 356
URL= /NULL.printer

HTTP field with binary

Parameters:

URL= /NULL.printer
field_length = 356 | 779
binary_count = 93 | 124

Note the **HTTP field with binary** event is a heuristic signature for the detection of buffer overflows and format string attacks. This event can therefore be generated in response to other types of attack, though as stated in the Network ICE support site the event often appears in pairs [9].

Other malicious web activity

If web sites are using password authentication, failed attempts to access them will generate the following event

HTTP login failed

Parameters:

count = varies (see below)

login = URL being attacked (e.g. /extranet)

A query the Security event log on Windows system for failure audit events (logon type 2) will identify the account used for the failed logons.

FTP Activity

It is likely that every day FTP scanning activity will be detected. Often attackers scan a ranges of IP addresses so if you have IDS agents installed on a number of Internet-facing machines you will see the following event reported over a short period of time from the same IP address by each agent in turn (assuming FTP services are not running).

FTP port probe

Parameters:

port = 21

reason = RSTsent or NOanswer

If your servers are hosting FTP services you may see attempts to guess legitimate passwords,

FTP login failed

Parameters:

count = 4

victim = IP Address

login = anonymous@ftp.microsoft.com

By default this event is generated after 4 failed logins in a configurable 3600-second period.

O/S Fingerprinting

From time to time the Internet-facing machine will be OS fingerprinted [10] from another machine on the Internet. Such activity can trigger the following events.

TCP OS fingerprint

Parameters:

port = varies (e.g. 21, 80 etc depending on open ports)

flags = varies (e.g. SF, SFPU depends on fingerprinting method)

options = varies (e.g. 3-0x;2-0x01;8-0x3F3F3F3F000000)

NMAP OS fingerprint

Parameters:

port = varies (e.g. 21)

flags = varies (e.g. S)

options = varies (e.g. 3-0x;2-0x01;8-0x3F3F3F3F000000)

Common BlackICE false positives seen on an internal Microsoft network

Unlike agents running on the DMZ web servers – exposed only to external attacks on port 21, 80 and 443 – agents running on an internal network will see a lot more activity across a broad range of ports. Identifying and classifying the nature of this activity – malicious or false positive – is a big challenge for IDS administrators.

Every internal network configuration is different so the purpose of this section is to point BlackICE IDS administrators in the general direction event classification. Ports used by different applications vary as much as the network activity generated by different applications.

Some of these events will be seen by DMZ server agents, though this will depend on the types of network traffic allowed into the DMZ from the internal network and other DMZs e.g. network backups, Enterprise monitoring systems etc.

Identifying and classifying these false positives allows the IDS administrator to use the built-in BlackICE facilities for managing false positives.

Such facilities include

- Using ICEcap policies to create policy issues that drop the severity of common false positive events.
- Defining trusted hosts, trusted issues and trust pairs (trusted issues from certain hosts) to prevent event generation in the first place.
- Modifying the thresholds beyond which an event is generated.

A discussion of these techniques is not covered in detail here.

Probes and Scans

A port probe event is generated when a failed connection is made to a network service. The connection fails because the service is not running, is temporarily unavailable or a firewall rule on the IDS agent rejects the connection request.

HTTP port probe

Parameters:

port = 80

reason = varies (e.g. RSTsent=connection rejected, Noanswer=no response)

Cause: Failed connections to TCP port 80.

Example(s): Windows 2000 can trigger these when mapping drives. Also seen if

web-based attacks (Nimda or Code Red) are directed against non-web DMZ servers.

NetBIOS port probe

Parameters:

port = 139

reason = varies (e.g. RST sent, No answer)

Cause: A connection to TCP port 139.

Example(s): Mapping a drive with 'Net Use' (or with Windows Explorer) to a machine when NetBIOS file and print services (on TCP 139) are unavailable.

SNMP port probe

Parameters:

port = 161

reason = varies (e.g. ICMP sent, Firewalled by Agent)

Cause: A failed connection to UDP port 161.

Example(s): Microsoft's SMS and Enterprise management and monitoring systems can generate many of these probes during data collection.

TCP port probe & UDP port probe

Parameters:

port = varies (port of service probed)

reason = varies (ICMP sent [UDP], RST sent [TCP], Firewalled, No answer)

Cause: Failed connections to services running on TCP/UDP ports that are unknown by the Black ICE agent.

Example(s): They will often be seen when legitimate services are too busy to respond to connection attempts. Examples include monitoring agents talking to collection servers, browsers connecting to busy secure web sites (TCP 443) and very commonly in Windows 2000 environments when machines probe the Direct Host port [11] or TCP 445.

TCP port scan & UDP port scan

Parameters:

port = varies (e.g. port 1 | port 2 | port 3 | port 4....)

reason = varies (ICMP sent [UDP], RST sent [TCP], Firewalled, No answer)

Cause: Triggered by a sequential connection to 4 unique TCP or UDP ports (this is configurable).

Example(s): Network backup agents communicating with backup servers or by network mapping tools.

Microsoft networking activity

MS share dump

Parameters:

(null)

Example(s): Seen frequently in a Microsoft domain environment - it can be

generated through browsing the share list on a domain machine in Network Neighbourhood.

SMB empty password

Parameters:

account = varies

share = \\MACHINENAME\SHARE

Cause: A connection made to a share with no password.

Examples: Automated services may connect to, say SMS or anti-virus update shares that have no password protection. Also seen if a user logged on with a Windows domain account connects to another Windows machine that is not part of the domain, but the credentials match local credentials (username and password).

MS security ID lookup

Parameters:

(null)

Example(s): Normal domain activity including viewing user rights in User Manager, viewing logged on users in Server Manager and opening remote event logs.

SMB login failed

Parameters:

count = varies (number of failed attempts - 4, 6 etc)

login = e.g. Administrator

victim = IP address

Cause: 4 failed logins within a configurable 3600-second period.

Example(s): Frequently seen if services (e.g. SMS, monitoring tools etc) are running as a user account and the password has changed or expired.

MS name lookup

Parameters:

(null)

Example(s): Generated during domain member to domain controller communication. Viewing user details with a domain management tool like Hyena can generate it (along with an ***MS security ID lookup*** event).

Network discovery/management activity

SNMP backdoor

Parameters:

community = varies (e.g. admin | openview | password etc)

Cause: SNMP connect to a machine with one of a list of default passwords.

Example(s): Your network uses default SNMP passwords

SNMP discovery broadcast

Parameters:

command = varies (e.g. community = public)

Cause: SNMP GET commands.

Examples: Enterprise management and monitoring systems broadcasts.

Other network activity

ICMP subnet mask request

Parameters:
(null)

Examples: Network management and monitoring discovery broadcasts.

RPC bad credentials

Parameters:
reason = varies (e.g. credlen&length=500)

Cause: Unusual sets of credentials that do not match the RPC specifications.

Example(s): Backup software such as Legato.

Ping sweep

Parameters:
(null)

Examples: Network management and monitoring systems when mapping networks.

Telnet abuse

Parameters:
port = varies (e.g. 25 | 80 | 100 etc)

Cause: Telnet connection attempts to FTP (21), SMTP (25), HTTP (80), POP (110) or IMAP (143).

Example(s): Testing to see if a service is running.

TCP SYN flood

Parameters:
percentfromintruder = percentage of SYN connects originating from one host

Cause: 100 failed TCP connections over a configurable 1-second period.

Example(s): Scanning tools, or services that were offline coming back online.

Creating a Custom BlackICE Attack Signature [12]

Custom attack signatures (or 'Intrusions') can be created for all Black ICE agents. The process differs slightly if the agents are standalone (BlackICE Defender) or part of an Enterprise deployment (using an ICEcap console).

The two issues to note are firstly that custom signatures will be overwritten if the agent software is updated, for example by downloading the latest version of Defender or by pushing the latest agent updates from the ICEcap console.

The second issue is that changing the configuration files may have a support implication with your reseller or vendor.

Attack signatures can be written that look for specific patterns in network traffic. The types of patterns include URLs, SMB filenames, FTP filenames, HTTP GET requests, HTTP PUT requests and so on.

The custom attack signature created below will trigger an event when a request to access a "payroll.txt" file over an SMB connection is seen by the IDS agent. Note that this procedure has been tested on agents running on NT machines only.

Creating a BlackICE Defender 2.5 Custom Attack Signature

- (1) Stop the BlackICE service and close the BlackICE GUI (tray icon)
- (2) Remove the read-only attribute from the 'issuelist.csv' file found in the /program files/Network ICE/BlackICE folder.
- (3) Open the 'issuelist.csv' file and add a row below (for example) issue 2009201 – the ISS Scan issue.
- (4) Enter an unused issue number of 2009202 and give the issue a name (say, **Payroll Access**). Enter a type of 0, an impact of 0, a pk-severity of -1, a di-severity of 4 (up to you), leave roots blank, add a class of Suspicious file and a summary of 'Someone is trying to access the Payroll file' i.e.

2009202,Payroll Access,0,0,-1,4,,Suspicious file,Someone is trying to access the Payroll file,,

- (5) Save the 'issuelist.csv' file and make it read-only again.
- (6) Open the 'blackice.ini' file also found under /program files/Network ICE/BlackICE folder and add the following line

smb.filename.2009202=*/payroll.txt

- (7) Restart the BlackICE service and the BlackICE GUI.
- (8) Create a c:\payroll.txt file, map a drive to the NT share \\machinename\c\$ from another machine. Open the payroll.txt file from the remote machine and check the GUI on the target machine for a **Payroll Access** event.

Creating an Enterprise BlackICE Agent 2.5 Custom Attack Signature

Carry out the following steps on the ICEcap console.

- (1) Stop the ICEcap service, BlackICE service and BlackICE GUI (if installed).

- (2) Edit the both the 'issuelist.csv' files found in the \program files\Network ICE\ICEcap\infobase\issues folder (not read-only) and the 'issuelist.csv' file found under \program files\Network ICE\ICEcap\versions\{agent version}\blackd folder (which is read-only).
- (3) Carry out steps 3, 4 as above on both 'issuelist.csv' files.
- (4) Make the agent 'issuelist.csv' file read-only again.
- (5) Restart the ICEcap, BlackICE services and BlackICE GUI (if installed).
- (6) Login to the web-based ICEcap console with administrative rights. Under the Agent Configuration screen of the target agent add a Custom parameter with a name of **smb.filename.2009202**, a value of ***/payroll.txt** and a comment of 'Someone is trying to access the Payroll file'.
- (7) Uninstall the remote agents and then reinstall them again from the ICEcap console using the Agent Install mechanism.
- (8) Carry out step 8 as above to test the custom attack signature. Look for the **Payroll Access** event in the BlackICE GUI of the local agent and also check the same event is recorded at the ICEcap console.

A small selection of other custom parameter examples include

```
ftp.filename.issuenumner=*/texthere
httpget.filename.issuenumner=*/texthere
email.subject.issuenumner=*/^Subject: Here
mimepattern.issuenumner=*.vbs
```

Note: As mentioned, your mileage will vary as any subsequent re-install or update of the agents will overwrite the 'issuelist.csv' file and therefore any custom attack signature you have defined. These custom attacks will need recreating.

Appendix – Summary of BlackICE false positives seen on an internal Microsoft network

| Event | Parameters | Possible cause |
|----------------------------|---|--|
| HTTP port probe | port = 80 | Attempted web connection to a machine without web services running. |
| NetBIOS port probe | port = 139 | Attempted drive mapping to a machine without NetBIOS services running. |
| SNMP port probe | port = 161 | Enterprise management & monitoring systems. |
| TCP/UDP port probes | port = varies (e.g. TCP 443 TCP 445) | Monitoring agents failing to connect to busy collection servers. Browsers failing to |

| | | |
|---------------------------------|---|--|
| | | connect to busy HTTPS services. Windows 2000 machines attempting direct host connections to their peers. |
| TCP/UDP port scans | port = varies (e.g. port1 port2 port3..) | Network backup agents communicating with busy backup servers |
| MS share dump | (null) | Browsing a share list on a machine |
| SMB empty password | account = varies share = varies | Connection to non-password protected shares |
| MS security ID lookup | (null) | Normal MS domain activity. Remote viewing of event logs, viewing user rights in user manager. |
| SMB login failed | count = varies login = varies victim = varies | Services running as user accounts and password has changed or expired. |
| MS name lookup | (null) | Normal MS domain activity. MS domain management tools. |
| SNMP backdoor | community = varies | Network using default SNMP passwords |
| SNMP discovery broadcast | command = varies | Enterprise management and monitoring system broadcasts. |
| ICMP subnet mask request | (null) | Network management and monitoring tools. |
| RPC bad credentials | reason = varies | Network backup agents communicating with backup servers. |
| Ping sweep | (null) | Network management and monitoring tools. |
| Telnet abuse | port = varies | Testing of service availability. |
| TCP SYN flood | percent from intruder = varies | Offline services returns online (e.g. email services). |

References

[1] Database of Intrusions detected by Network ICE
<http://advice.networkice.com/Advice/Intrusions/default.htm>

[2] SANS reading room: Incident Handling and Forensics
http://www.sans.org/infosecFAQ/incident/incident_list.htm

[3] Firewall-1 Implicit Rules: Security Advisory
<http://www.codetalker.com/advisories/misc/dil981024.html>

[4] "Code Red" Worm Exploiting Buffer Overflow In IIS Indexing Service DLL
<http://www.cert.org/advisories/CA-2001-19.html>

[5] Code Red Scanner from eEye Digital Security
<http://www.eeye.com/html/Research/Tools/codered.html>

[6] A Snapshot of Global Internet Worm Activity
<http://www.monkey.org/~dugsong/papers/worms/>

[7] Nimda Worm
<http://www.cert.org/advisories/CA-2001-26.html>

[8] Buffer Overflow Vulnerability in Microsoft IIS 5.0
<http://www.cert.org/advisories/CA-2001-10.html>

[9] HTTP field with Binary
<http://advice.networkice.com/advice/Intrusions/2000646/default.htm>

[10] Remote OS detection via TCP/IP Stack Finger Printing
<http://www.insecure.org/nmap/nmap-fingerprinting-article.html>

[11] Microsoft Windows 2000 TCP/IP Implementation Details
<http://www.microsoft.com/technet/itsolutions/network/deploy/depovg/tcpip2k.asp>

[12] Discussions with BlackICE support staff.

© 2011 SANS Institute, Author retains full rights.

Upcoming Training

Click Here to
{Get CERTIFIED!}



| | | | |
|--|---------------------------------|-----------------------------|----------------|
| SANS Las Vegas 2019 | Las Vegas, NV | Jan 28, 2019 - Feb 02, 2019 | Live Event |
| SANS Security East 2019 | New Orleans, LA | Feb 02, 2019 - Feb 09, 2019 | Live Event |
| Security East 2019 - SEC401: Security Essentials Bootcamp Style | New Orleans, LA | Feb 04, 2019 - Feb 09, 2019 | vLive |
| SANS Northern VA Spring- Tysons 2019 | Tysons, VA | Feb 11, 2019 - Feb 16, 2019 | Live Event |
| SANS Anaheim 2019 | Anaheim, CA | Feb 11, 2019 - Feb 16, 2019 | Live Event |
| SANS Secure Japan 2019 | Tokyo, Japan | Feb 18, 2019 - Mar 02, 2019 | Live Event |
| SANS Scottsdale 2019 | Scottsdale, AZ | Feb 18, 2019 - Feb 23, 2019 | Live Event |
| SANS New York Metro Winter 2019 | Jersey City, NJ | Feb 18, 2019 - Feb 23, 2019 | Live Event |
| SANS Dallas 2019 | Dallas, TX | Feb 18, 2019 - Feb 23, 2019 | Live Event |
| Open-Source Intelligence Summit & Training 2019 | Alexandria, VA | Feb 25, 2019 - Mar 03, 2019 | Live Event |
| SANS Reno Tahoe 2019 | Reno, NV | Feb 25, 2019 - Mar 02, 2019 | Live Event |
| Mentor Session @Work - SEC401 | Raleigh, NC | Feb 27, 2019 - Mar 06, 2019 | Mentor |
| SANS Baltimore Spring 2019 | Baltimore, MD | Mar 02, 2019 - Mar 09, 2019 | Live Event |
| Community SANS Indianapolis SEC401 | Indianapolis, IN | Mar 04, 2019 - Mar 09, 2019 | Community SANS |
| SANS Secure India 2019 | Bangalore, India | Mar 04, 2019 - Mar 09, 2019 | Live Event |
| Baltimore Spring 2019 - SEC401: Security Essentials Bootcamp Style | Baltimore, MD | Mar 04, 2019 - Mar 09, 2019 | vLive |
| SANS St. Louis 2019 | St. Louis, MO | Mar 11, 2019 - Mar 16, 2019 | Live Event |
| SANS Secure Singapore 2019 | Singapore, Singapore | Mar 11, 2019 - Mar 23, 2019 | Live Event |
| SANS London March 2019 | London, United Kingdom | Mar 11, 2019 - Mar 16, 2019 | Live Event |
| SANS San Francisco Spring 2019 | San Francisco, CA | Mar 11, 2019 - Mar 16, 2019 | Live Event |
| Mentor Session - SEC401 | Fredericksburg, VA | Mar 12, 2019 - May 14, 2019 | Mentor |
| SANS Norfolk 2019 | Norfolk, VA | Mar 18, 2019 - Mar 23, 2019 | Live Event |
| SANS Munich March 2019 | Munich, Germany | Mar 18, 2019 - Mar 23, 2019 | Live Event |
| SANS Secure Canberra 2019 | Canberra, Australia | Mar 18, 2019 - Mar 23, 2019 | Live Event |
| SANS vLive - SEC401: Security Essentials Bootcamp Style | SEC401 - 201903, | Mar 19, 2019 - Apr 25, 2019 | vLive |
| SANS 2019 - SEC401: Security Essentials Bootcamp Style | Orlando, FL | Apr 01, 2019 - Apr 06, 2019 | vLive |
| SANS 2019 | Orlando, FL | Apr 01, 2019 - Apr 08, 2019 | Live Event |
| Community SANS Raleigh SEC401 | Raleigh, NC | Apr 01, 2019 - Apr 06, 2019 | Community SANS |
| SANS London April 2019 | London, United Kingdom | Apr 08, 2019 - Apr 13, 2019 | Live Event |
| Blue Team Summit & Training 2019 | Louisville, KY | Apr 11, 2019 - Apr 18, 2019 | Live Event |
| SANS Riyadh April 2019 | Riyadh, Kingdom Of Saudi Arabia | Apr 13, 2019 - Apr 18, 2019 | Live Event |